# ZC1AZ13

composition

Contact operation

Contacts material

Positive opening

# Limit switch contact block, Limit switches XC Standard, 1NC+1 NO, make before brake



#### Main Range of Product OsiSense XC Series name Special format Limit switch contact block **Product or Component** Type ZC1A Device short name **Product Compatibility** XC1AC13. Electrical connection Screw-clamp terminals 1 x 0.5...2 x 2.5 mm<sup>2</sup> Number of poles Contacts type and 1 NO + 1 NC

Slow-break, make before break

Silver plated contacts

Without

Complementary

Contacts insulation form	Zb
Minimum actuation speed	6 m/min
Maximum resistance across terminals	8 mOhm IEC 60255-7 category 3
[Ithe] conventional enclosed thermal current	10 A
[Ui] rated insulation voltage	500 V ACIEC 60947-5-1 500 V ACNF C 20-040 600 V DCIEC 60947-5-1 600 V DCNF C 20-040 600 V ACCSA C22.2 No 14 600 V DCCSA C22.2 No 14
Short-circuit protection	10 A cartridge fuse gG
Electrical durability	1000000 Cycles, AC-15 110 V, 900 VA 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 1000000 Cycles, AC-15 230 V, 1900 VA 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 1000000 Cycles, AC-15 48 V, 450 VA 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 1000000 Cycles, DC-13 110 V, 100 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 1000000 Cycles, DC-13 230 V, 95 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 1000000 Cycles, DC-13 48 V, 100 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 3000000 Cycles, AC-15 110 V, 350 VA 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 3000000 Cycles, AC-15 230 V, 430 VA 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 3000000 Cycles, AC-15 48 V, 170 VA 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 3000000 Cycles, DC-13 110 V, 40 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 3000000 Cycles, DC-13 230 V, 33 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C 3000000 Cycles, DC-13 48 V, 35 W 60 cyc/mn 0.5 IEC 60947-5-1 appendix C

### Ordering and shipping details

22449-LIMIT SWITCHES, ACCESSORIES	
Т	
3389110322705	
1	
1.76 oz (50.0 g)	
No	
FR	
	T 3389110322705 1 1.76 oz (50.0 g) No

## **Packing Units**

3		
Unit Type of Package 1	PCE	
Package 1 Height	0.91 in (2.3 cm)	
Package 1 width	3.98 in (10.1 cm)	
Package 1 Length	3.35 in (8.5 cm)	
Unit Type of Package 2	S02	
Number of Units in Package 2	50	
Package 2 Weight	6.26 lb(US) (2.838 kg)	
Package 2 Height	5.91 in (15 cm)	
Package 2 width	11.81 in (30 cm)	
Package 2 Length	15.75 in (40 cm)	

# Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS  Declaration
Mercury free	Yes
RoHS exemption information	₫Yes

#### Contractual warranty

Contractad Warranty	
Warranty	18 months