

## EPIC® MC 2.5 machined contacts

For inserts and modules of the EPIC® rectangular connectors

The machined contacts for conductor cross-section from 0.5 to 4 mm<sup>2</sup> are available as female and male pins.

### Info

silver plated and passivated contacts



### Technical Data

Classification ETIM 5:

ETIM 5.0 Class-ID: EC000796

ETIM 5.0 Class-Description: Contact for industrial connectors

Classification ETIM 6:

ETIM 6.0 Class-ID: EC000796

ETIM 6.0 Class-Description: Contact for industrial connectors

### Note

Photographs and graphics are not to scale and do not represent detailed images of the respective products.  
Prices are net prices without VAT and surcharges. Sale to business customers only.

**EPIC® MC 2.5 machined contacts**

Article number	Article description	Version	Conductor cross-section (mm <sup>2</sup> )	Cross-section identification	Surface	Stripping length (mm)	Pieces / PU
Contacts							
1121300C	MC 2.5 machined	male	0.5	-	Ag	7.8	100
1121800C	MC 2.5 machined	female	0.5	-	Ag	7.8	100
1121310C	MC 2.5 machined	male	1	1	Ag	7.8	100
1121810C	MC 2.5 machined	female	1	1	Ag	7.8	100
1121320C	MC 2.5 machined	male	1.5	2	Ag	7.8	100
1121820C	MC 2.5 machined	female	1.5	2	Ag	7.8	100
1121330C	MC 2.5 machined	male	2.5	3	Ag	7.8	100
1121830C	MC 2.5 machined	female	2.5	3	Ag	7.8	100
1121340C	MC 2.5 machined	male	4	-	Ag	7.8	100
1121840C	MC 2.5 machined	female	4	-	Ag	7.8	100