



Product Description

Speaker Cable, 4 Conductor 12 AWG (168 x 34) Oxygen-Free Bare Copper (High Conductivity), PE Insulation, PVC Jacket, CM, Direct Burial, Flexible

Technical Specifications

Product Overview

itable App	ications:	Speaker Ca	ble; Direct	Burial; Indoor/Ou	tdoor Ho	ome Theater; In-	-Wall Speaker; Ou	itdoor Speaker
struct	ion Details							
ductor								
Element	Number of Element	t Size	Stranding	Ν	Aaterial			
onductor(s)	4	12 AWG	168x34	BC - Bare Cop	per (High	Conductivity)		
ulation								
Element	Material	Nom. Thick	ness No	m. Insulation Dia	ameter	Color C	ode	
nductor(s)	PE - Polyethylene	0.018 in (0.46	6 mm) 0.1	4 in (3.6 mm)		Black, Red, Wh	nite, Green	
er Jacket								
Mate	rial Nom. Th	ickness N	Nom. Diam	eter				
C - Polyvii	nyl Chloride 0.043 in	(1.1 mm) 0.4	423 in (10.7	7 mm)				
all Cable	e Diameter (Nominal):	0.423 in (10	.7 mm)					
trical	Characteristics							
ctricals								
Element	Nom. Conductor De		apacitance /ft (73.2 pF/	e Cond-to-Cond	Nom.	Velocity of Pro	·	Current
iddotoi (0)		22.0 pr	n (10.2 pi)	,,	0070		247 (11) 0 001	
ige								
Voltage I								
	,L3)							
:hanic	al Characteristic	s						
nperature								
. Tempera	ture Operating							
С	-20°C To +75°C							
		_						
nd Radius		1						
	lin. Installation Min.							
d Radius ationary M : in (110 m								
ationary N	m) 4.2 in (110 mm)	338 lbs (153	3 kg)					

Environmental Suitability:	Indoor (Not Riser or Plenum), Indoor, Outdoor, Burial
Flammability / Reaction to Fire:	UL 1685 UL loading
NEC / UL Compliance:	Article 725, Article 800, CL3, CM
CEC / C(UL) Compliance:	СМ
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)
Plenum Number:	6002UE

Product Notes

Jacket has ROOM 1 2 3 4 5 6 7 8 9 0 ZONE A B C D printed on it.

History

Update and Revision:

Revision Number: 0.478 Revision Date: 04-14-2023

Part Numbers

Variants

Item #	Color	Putup Type	Length	UPC
1312A 010500	Black	Reel	500 ft	612825111672
1312A 0101000	Black	Reel	1,000 ft	612825111665
1312A 008500	Gray	Reel	500 ft	612825111658
1312A 0081000	Gray	Reel	1,000 ft	612825111641
1312A 1SL500	White 1SL	Reel	500 ft	612825111696
1312A 1SL1000	White 1SL	Reel	1,000 ft	612825111689

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.