



# Product: FLEX MODULE USOC

Flex Modular Jack, RJ45, MDVO Style

# Product Description

Flex Module USOC are available in several colors.

# **Technical Specifications**

# **Product Overview**

Suitable Applications:	Voice Applications
Physical Characteristics (Overall)	

Height:	0.85 in	
Width:	0.77 in	
Depth:	1.35 in	
Wiring Scheme:	USOC	
Packaging:	Individually packaged in a plastic bag. Standard pack of 50 units.	
Weight:	0.014 lbs	

# Connectors

#### Materials

Description	Material	Туре
Front Connection	Copper Alloy with 50 $\mu$ inch Gold over Nickel	Lead Frame
Rear Connection	Copper Alloy with Nickel Plating	IDC
Connector Body	Plastic - UL940V-0	

# **Electrical Characteristics**

Dielectric Strength:	1,000 V RMS @ 60 Hz for 1 minute
Current Rating:	1.500 A
Insulation Resistance:	500 M-Ohm Minimum
Max Contact Resistance:	20 mOhm
Termination Resistance:	2.5 mOhm

# **Temperature Range**

Installation Temperature Range:	-10°C To +60°C
Storage Temperature Range:	-40°C To +70°C
Operating Temperature Range:	-10°C To +60°C

# **Mechanical Characteristics**

Footprint/Type:	MDVO
Tool Compatibility:	Belden 110 Connecting Tool, MediaFlex Termination Station
Plug /Jack Compatibility:	RJ45, RJ11
Termination Front Connection:	Mated Connection
Termination Front Connection Durability:	1,000 cycles
Termination Rear Connection:	Gas Tight IDC Connection

Termination Rear Connection Durability:	20 terminations
Connector/Hardware Retention:	20 lbs
Plug/Connector Retention:	11.250 lbs

#### **Standards**

Other Standards:

# FCC Part 68, Subpart F, IEC 60603-7

# **Applicable Environmental and Other Programs**

Environmental Space:	Indoor
EU Directive 2002/95/EC (RoHS):	Yes
MII Order #39 (China RoHS):	EUP 50

# Flammability, LS0H, Toxicity Testing

Safety Listing:

ACA, c(UL)us Listed

# **Related Part Numbers**

Related Parts:

Compatible with Interface and MDVO Style Faceplates, Adapters, Boxes and Patch Panels

#### Variants

Item #	Color	Packaging
AX101034	Almond	Single Pack
AX101036	Black	Single Pack
AX101033	Gray	Single Pack
AX102565	lvory	Single Pack
AX101041	TIA Blue	Single Pack
AX101043	TIA Brown	Single Pack
AX101040	TIA Green	Single Pack
AX101037	TIA Orange	Single Pack
AX101042	TIA Purple	Single Pack
AX101038	TIA Red	Single Pack
AX101039	TIA Yellow	Single Pack
AX101035	White	Single Pack

#### **Product Notes**

Included Parts:	1 Clear Protective Cap
Notes:	Please see Installation Guide PX101565

# History

Update and Revision:

Revision Number: 0.197 Revision Date: 05-10-2023

#### © 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or guality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.