SIEMENS

Data sheet

3SU1001-0BB50-0AA0-Z Y12



Illuminated pushbutton, 22 mm, round, plastic, blue, pushbutton, raised momentary contact type, with laser labeling, lower case

product brand name	SIRIUS ACT	
product designation	Illuminated pushbuttons	
design of the product	Actuating/signaling element	
product type designation	- 3SU1	
product line	Plastic, black, 22 mm	
Enclosure		
number of command points	1	
Actuator		
design of the actuating element	Raised button	
principle of operation of the actuating element	momentary contact type	
product extension optional		
light source	Yes	
contact module	Yes	
color of the actuating element	blue	
material of the actuating element	plastic	
shape of the actuating element	round	
outer diameter of the actuating element	29.5 mm	
marking of the actuating element	Customized labeling, text in lower case letters	
Front ring		
product component front ring	Yes	
design of the front ring	Standard	
material of the front ring	plastic	
color of the front ring	black	
General technical data		
protection class IP	IP66, IP67, IP69(IP69K)	
degree of protection NEMA rating	1, 2, 3, 3R, 4, 4X, 12, 13	
shock resistance		
• acc. to IEC 60068-2-27	Sinusoidal half-wave 50g / 11 ms	
 for railway applications acc. to DIN EN 61373 	Category 1, Class B	
vibration resistance		
• acc. to IEC 60068-2-6	10 500 Hz: 5g	
 for railway applications acc. to DIN EN 61373 	Category 1, Class B	
operating frequency maximum	3 600 1/h	
mechanical service life (switching cycles) typical	3 000 000	
reference code acc. to IEC 81346-2	S	
Ambient conditions		
ambient temperature during operation	-25 +70 °C	

 ambient temperature during storage 	-40 +80 °C
environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95 %)
Installation/ mounting/ dimensions	
height	29.5 mm
width	29.5 mm
shape of the installation opening	round
mounting diameter	22.3 mm
positive tolerance of installation diameter	0.4 mm
mounting height	16.2 mm
installation width	29.5 mm
installation depth	24.3 mm
Certificates/ approvals	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1001-0BB50-0AA0-Z Y12

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1001-0BB50-0AA0-Z Y12

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1001-0BB50-0AA0-Z Y12

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <u>http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1001-0BB50-0AA0-Z Y12&lang=en</u>

last modified:

12/21/2020 🖸