



## Main

|                           |  |
|---------------------------|--|
| Range of Product          | Telemecanique Emergency stop rope pull switches XY2C |
| Product or Component Type | Latching emergency stop rope pull switch             |
| Device short name         | XY2CE  |
| Housing colour            | Red RAL 3000   |
| Overtoltage category      | Class I EN/IEC 61140<br>Class I NF C 20-030          |

## Complementary

|  |   |
|--|---|
| Local signalling                             | Without pilot light   |
| Number of cables                             | 1   |
| Trigger cable maximum length                 | 229.66 ft (70 m)  |
| Body Material                                | Zamak   |
| Cover Material                               | Stainless steel   |
| Reset  | By key-release push-button  |
| Trigger cable anchor point                   | RH side   |
| Connections - terminals                      | Screw clamp terminal, 1 x 0.5...2 x 1.5 mm <sup>2</sup>   |
| Tightening torque                            | 7.08...10.62 lbf.in (0.8...1.2 N.m)   |
| Cable entry number                           | 3   |
| Safety level                                 | Can reach PL = e with the appropriate monitoring system and correctly wired EN/ISO 13849-1<br>Can reach category 4 with the appropriate monitoring system and correctly wired EN/ISO 13849-1<br>Can reach SIL 3 with the appropriate monitoring system and correctly wired EN/IEC 61508 |
| Safety reliability data                      | B10d = 300000 value given for a life time of 20 years limited by mechanical or contact wear IEC 60947-5-5   |
| Marking                                      | CE  |
| Mechanical durability                        | 60000 cycles  |
| Distance between cable supports              | 16.40 ft (5 m)  |
| [Ie] rated operational current               | 3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A<br>0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A   |
| [Ithe] conventional enclosed thermal current | 10 A  |
| [Ui] rated insulation voltage                | 500 V 3)EN/IEC 60947-1<br>300 VUL 508<br>300 VCSA C22.2 No 14   |
| [Uimp] rated impulse withstand voltage       | 6 kV EN/IEC 60947-1   |
| Positive opening                             | With EN/IEC 60947-5-1   |
| Maximum resistance across terminals          | 25 MOhm EN/IEC 60255-7 category 3<br>25 MOhm NF C 93-050 method A   |
| Short-circuit protection                     | 10 A cartridge fuse gG EN/IEC 60269   |
| Terminals description ISO n°1                | (21-22)NC<br>(11-22)NC  |
| Net Weight                                   | 3.24 lb(US) (1.47 kg)   |
| Compatibility code                           | XY2CE   |

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | UL 508<br>CSA C22.2 No 14<br>EN/IEC 60947-5-5<br>EN/IEC 60947-5-1<br>Work equipment directive 2009/104/EC<br>EN/ISO 13850<br>EN/IEC 60204-1<br>Machinery directive 2006/42/EC |
| Product certifications                | UL category NISD emergency stop devices<br>CSA<br>CCC   |
| Protective treatment                  | TC  |
| Ambient Air Temperature for Operation | -40...158 °F (-40...70 °C)  |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)  |
| Vibration resistance                  | 10 gn 10...300 Hz)EN/IEC 60068-2-6  |
| Shock resistance                      | 50 gn 11 ms EN/IEC 60068-2-27   |
| IP degree of protection               | IP65 IEC 60529  |

## Ordering and shipping details

|                       |                                 |
|-----------------------|---------------------------------|
| Category              | 22441-LIMIT SWITCHES,CABLE PULL |
| Discount Schedule     | T                               |
| GTIN                  | 3389118133013                   |
| Nbr. of units in pkg. | 1                               |
| Package weight(Lbs)   | 3.49 lb(US) (1.585 kg)          |
| Returnability         | No                              |
| Country of origin     | MA                              |

## Packing Units

|                        |                 |
|------------------------|-----------------|
| Unit Type of Package 1 | PCE             |
| Package 1 Height       | 3.54 in (9 cm)  |
| Package 1 width        | 5.91 in (15 cm) |
| Package 1 Length       | 7.87 in (20 cm) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>  |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|