SIEMENS

Data sheet

3SU1031-0AA50-0AA0-Z X90



Illuminated pushbutton, 22 mm, round, plastic with metal front ring, blue, pushbutton, flat, latching, Push-to-release mechanism, Z=100-unit packaging

product brand name SIRIUS ACT product designation Illuminated pushbuttons design of the product Actuating/signaling element product type designation 3SU1 product line Plastic with metal front ring, matt, 22 mm Enclosure 1 Actuator 4ctuator design of the actuating element Flat button			
design of the product Actuating/signaling element product type designation 3SU1 product line Plastic with metal front ring, matt, 22 mm Enclosure 1 number of command points 1 Actuator 1			
product type designation 3SU1 product line Plastic with metal front ring, matt, 22 mm Enclosure 1 number of command points 1 Actuator 1			
product line Plastic with metal front ring, matt, 22 mm Enclosure 1 number of command points 1 Actuator 1			
Enclosure number of command points 1 Actuator			
number of command points 1 Actuator 1			
Actuator			
design of the actuating element Flat button	Actuator		
principle of operation of the actuating element latching			
product extension optional			
light source Yes			
contact module Yes			
color of the actuating element blue			
material of the actuating element plastic			
shape of the actuating element round			
outer diameter of the actuating element 29.5 mm			
type of unlocking device push-to-unlatch mechanism			
Front ring			
product component front ring Yes			
design of the front ring Standard			
material of the front ring Metal, matt			
color of the front ring sand gray			
General technical data			
protection class IP IP66, IP67, IP69(IP69K)			
degree of protection NEMA rating 1, 2, 3, 3R, 4, 4X, 12, 13			
shock resistance			
according to IEC 60068-2-27 sinusoidal half-wave 15g / 11 ms			
for railway applications according to EN 61373 Category 1, Class B			
vibration resistance			
• according to IEC 60068-2-6 10 500 Hz: 5g			
for railway applications according to EN 61373 Category 1, Class B			
operating frequency maximum 1 800 1/h			
mechanical service life (switching cycles) typical 500 000			
reference code according to IEC 81346-2 S			
Substance Prohibitance (Date) 10/01/2014			
Ambient conditions			
ambient temperature			
• during operation -25 +70 °C			

during storage	-40 +80 °C	
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3, 3K6 (with relative air humidity of 10 95%)	
Installation/ mounting/ dimensions		
height	29.5 mm	
width	29.5 mm	
shape of the installation opening	round	
mounting diameter	22.3 mm	
positive tolerance of installation diameter	0.4 mm	
mounting height	11 mm	
installation width	29.5 mm	
installation depth	24.3 mm	
Certificates/ approvals		

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1031-0AA50-0AA0-Z X90

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1031-0AA50-0AA0-Z X90

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/3SU1031-0AA50-0AA0-Z X90

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1031-0AA50-0AA0-Z X90&lang=en

last modified:

1/26/2022 🖸