## **SIEMENS**

## **Data sheet**

## 6GK5124-0BA00-3AR3

SCALANCE XR124WG; Unmanaged IE switch; 19" rack; 24 x 10/100 Mbit/s electrical ports; LED diagnostics; power supply 240 V AC (85 - 264 V).



product type designation	SCALANCE XR124
transfer rate	
transfer rate	10 Mbit/s, 100 Mbit/s
interfaces / for communication / integrated	
number of electrical connections	
<ul> <li>for network components or terminal equipment</li> </ul>	24; RJ45
number of 10/100 Mbit/s RJ45 ports / integrated	24
interfaces / other	
number of electrical connections	
<ul><li>for power supply</li></ul>	1
type of electrical connection	
<ul><li>for power supply</li></ul>	2-pole terminal block
supply voltage, current consumption, power loss	
product component / connection for redundant voltage	Yes
supply	
type of voltage supply / redundant power supply unit	No
type of voltage / 1 / of the supply voltage	
<ul><li>supply voltage / 1 / rated value</li></ul>	240 V
<ul><li>power loss [W] / 1 / rated value</li></ul>	7.5 W
<ul><li>supply voltage / 1 / rated value</li></ul>	85 264 V
<ul><li>consumed current / 1 / maximum</li></ul>	0.075 A
<ul> <li>type of electrical connection / 1 / for power supply</li> </ul>	2-pole terminal block
<ul> <li>product component / 1 / fusing at power supply input</li> </ul>	Yes
ambient conditions	
ambient temperature	
<ul> <li>during operation</li> </ul>	0 60 °C
<ul> <li>during storage</li> </ul>	-40 +85 °C
during transport	-40 +85 °C
relative humidity	
<ul> <li>at 25 °C / without condensation / during operation /</li> </ul>	95 %
maximum	
protection class IP	IP30
design, dimensions and weights	
design	19" rack
width	482.6 mm
height	43.6 mm
depth	177 mm
net weight	3.3 kg
fastening method	

40 in the installation	V	
19-inch installation	Yes	
35 mm top hat DIN rail mounting	No	
<ul><li>wall mounting</li><li>S7-300 rail mounting</li></ul>	No No	
S7-1500 rail mounting     S7-1500 rail mounting	No	
product features, product functions, product components		
cascading in cases of star topology	any (depending only on signal propagation time)	
product functions / management, configuration, engineering		
product function	"9	
multiport mirroring	No	
• CoS	Yes	
product function / switch-managed	No	
product functions / redundancy		
product function		
<ul> <li>Parallel Redundancy Protocol (PRP)/operation in the PRP-network</li> </ul>	Yes	
<ul> <li>Parallel Redundancy Protocol (PRP)/Redundant Network Access (RNA)</li> </ul>	No	
standards, specifications, approvals		
standard		
<ul> <li>for safety / from CSA and UL</li> </ul>	UL 60950-1, CSA C22.2 No. 60950-1	
<ul> <li>for emitted interference</li> </ul>	EN 61000-6-4 (Class B)	
for interference immunity	EN 61000-6-2	
reference code		
<ul> <li>according to IEC 81346-2</li> </ul>	KF	
• according to IEC 81346-2:2019	KFE	
standards, specifications, approvals / CE		
certificate of suitability / CE marking	Yes	
standards, specifications, approvals / other		
certificate of suitability		
• C-Tick	Yes	
• KC approval	Yes	
railway application in accordance with EN 50155	No T	
related to FCC     FCC Port 15 Section B. Close b.		
FCC, Part 15, Section B, Class b further information / internet-Links	Yes	
Internet-Link		
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/tia-selection-tool	
to web page. Selection and TIA Selection Tool     to website: Industrial communication	http://www.siemens.com/simatic-net	
to website: Industrial communication     to website: Industry Mall	https://mall.industry.siemens.com	
to website: Information and Download Center	http://www.siemens.com/industry/infocenter	
to website: Image database	http://automation.siemens.com/bilddb	
to website: Image database     to website: CAx-Download-Manager	http://www.siemens.com/cax	
to website: Industry Online Support	https://support.industry.siemens.com	
security information	- A CONTROL OF THE CO	
security information	Siemens provides products and solutions with industrial security	
	functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com. (V3.4)	
last modified:	7/8/2022 🗗	