

Product data sheet

Characteristics


GV2G445

Linergy FT, Comb busbar, 63A, 4 tap-offs, 45mm pitch



Product availability: Stock - Normally stocked in distribution facility

Price*: 34.20 USD



Main

| | |
|---|---|
| Range | Linergy |
| Product name | FT |
| Device short name | GV2G |
| Product or Component Type | Comb busbar |
| Accessory / separate part category | Connection accessory |
| Poles description | 3P |
| Range compatibility | TeSys Deca TeSys GV2 TeSys K TeSys U |
| Number of tap-offs | 4 |
| [Ith] conventional free air thermal current | 63 A |
| Connection pitch | 1.77 In (45 mm) |

Complementary

| | |
|-------------------------------|------------------------|
| Mounting Location | On terminal |
| [Ui] Rated Insulation Voltage | 690 V |
| Length | 7.05 In (179 mm) |
| Net Weight | 0.17 Lb(US) (0.077 kg) |

Ordering and shipping details

| | |
|-------------------|----------------------------------|
| Category | 22367-MANUAL STR PROTECTOR - GV2 |
| Discount Schedule | I11 |
| GTIN | 3389110555882 |
| Returnability | Yes |
| Country of origin | RO |

Packing Units

| | |
|------------------------------|----------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 0.39 In (1.000 cm) |
| Package 1 Width | 1.38 In (3.500 cm) |
| Package 1 Length | 7.09 In (18.000 cm) |
| Package 1 Weight | 2.75 Oz (78.000 g) |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 60 |
| Package 2 Height | 5.91 In (15.000 cm) |
| Package 2 Width | 5.91 In (15.000 cm) |
| Package 2 Length | 15.75 In (40.000 cm) |
| Package 2 Weight | 10.87 Lb(US) (4.930 kg) |
| Unit Type of Package 3 | P06 |
| Number of Units in Package 3 | 1920 |
| Package 3 Height | 29.53 In (75.000 cm) |
| Package 3 Width | 23.62 In (60.000 cm) |
| Package 3 Length | 31.50 In (80.000 cm) |
| Package 3 Weight | 364.78 Lb(US) (165.460 kg) |


Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Sets of Busbars GV2G445, GV2G454, GV2G472, with Terminal Block GV2G05



| | l | p |
|---------------------|-----|----|
| GV2G445 (4 x 45 mm) | 179 | 45 |
| GV2G454 (4 x 54 mm) | 206 | 54 |
| GV2G472 (4 x 72 mm) | 260 | 72 |

| Number of tap-offs | a | | | |
|--------------------|-----|-----|-----|-----|
| | 5 | 6 | 7 | 8 |
| GV2G445 | 224 | 269 | 314 | 359 |
| GV2G454 | 260 | 314 | 368 | 422 |
| GV2G472 | 332 | 404 | 476 | 548 |

Product Life Status : **Commercialised**