

Cat5e Retractable (UTP) Ethernet Cable (RJ45 M/M) - Black, 4 ft. (1.22 m)

MODEL NUMBER: N009-004-R



Highlights

- Ideal for connecting the RJ45 network port on your notebook to a network
- Cables extend easily and retract automatically

System Requirements

- PC/Notebook with RJ45 Ethernet Port
- Network Jack with RJ45 Ethernet Port

Package Includes

- 4-ft. (1.22 m) Retractable RJ45 M/M Cable for Laptop Ethernet Port

Description

Tired of carrying all those loose cords around? When you're an on-the-go business person with no time to spare, who wants to carry all those loose laptop cords with you while traveling? Eliminate all those worries with the retractable RJ45 Ethernet Patch Cable. It fits easily in your notebook case or pocket and extends up to 4-ft. (1.22 m) in length and gracefully retracts into a small reel. RJ45 male to male connectors.

Features

- Automatic spring retractable cord
- Great alternative to carrying loose network cables
- Ethernet 802.3 compliant

Specifications

OVERVIEW	
UPC Code	037332131706
Technology	Cat5/5e
POWER	
Power Over Cable (PoC) Support	No
PHYSICAL	
Cable Jacket Color	Black
Cable Jacket Material	PVC
Cable Shielding	UTP

Cable Outer Diameter (OD)	0.5*8.0mm
Conductor Material	Stranded Copper
Conductor Gauge	32 AWG
Cable Length (ft.)	4
Cable Length (m)	1.22
Cable Length (in.)	51.2
Cable Length (cm)	121.9
Shipping Dimensions (hwd / in.)	0.25 x 0.25 x 1.00
Shipping Dimensions (hwd / cm)	0.64 x 0.64 x 2.54
Shipping Weight (lbs.)	0.05
Shipping Weight (kg)	0.02
ENVIRONMENTAL	
Operating Temperature Range	14° to 104°F (-10° to 40°C)
Storage Temperature Range	5° to 122°F (-15° to 50°C)
Operating Humidity Range	0% to 90% RH, Non-Condensing
Storage Humidity Range	0% to 90% RH, Non-Condensing
COMMUNICATIONS	
Bandwidth per TIA Standard	100 MHz
Maximum Bandwidth as Tested	350 MHz
Network Compatibility	1 Gbps (Gigabit)
IEEE Standards Supported	802.3ab
CONNECTIONS	
Side A - Connector 1	RJ45 (MALE)
Side B - Connector 1	RJ45 (MALE)
Crossover Wiring	No
Contact Plating	Gold
Connector Type	Molded
Wiring Configuration	EIA/TIA 568B
Angled Connector	No
FEATURES & SPECIFICATIONS	
Antibacterial	No
IP68 Rated	No
Snagless Connector	No

TRIPP-LITE

by **EAT•N**

1000 Eaton Boulevard
Cleveland, OH 44122
United States

IP20 Rated	No
STANDARDS & COMPLIANCE	
Product Compliance	RoHS; IEEE 802.3ab 1000Base-T; REACH
WARRANTY & SUPPORT	
Product Warranty Period (Worldwide)	Lifetime limited warranty

TRIPP-LITE

by **EAT•N**

© 2023 Eaton. All Rights Reserved.
Eaton is a registered trademark. All other trademarks
are the property of their respective owners.