

## 10Gb Rigid Industrial Duplex Multimode 50/125 OM3 Fiber Patch Cable (LC/LC) - IP68, Aqua, 5 m (16.4 ft.)

MODEL NUMBER: N820-05M-IND



Connects fiber optic Ethernet equipment in industrial environments that require protection against dust and moisture.

### Features

**10G Duplex Multimode Cable Designed for Outdoor or Harsh Indoor Environments** This 16.4-foot (five-meter) 50/125 OM3 LC/LC IP68-rated outdoor cable is ideal for connecting 10G Ethernet fiber networks in outdoor applications and other areas where protection from harsh elements is essential, such as factories, warehouses, recycling plants, machine shops and other dusty environments. The rigid, durable cable and small-form-factor LC duplex connectors withstand dust, debris and moisture that could threaten your IT infrastructure. Included dust caps are located at both ends for protection from dust and debris when the connectors are not in use.

**IP68 Rating Denotes Resistance to Dust and Water** The fiber cable is 100% protected against dust and able to endure immersion in 1.5 meters of water for up to 60 minutes with no damage or decline in performance. Concentration of water moisture in fiber connectors will lead to glass damage and can severely disrupt or halt performance of optical cables. For applications that require IP68 protection, use the industrial cable with a N206-SB01-IND surface-mount box and an N455-BC01-IND bulkhead coupler. If only IP44 protection against splashing water from all directions is required, pair the cable with a N206-FP01-IND, N206-FP02-IND or N206-FP04-IND metal wall plate and an N455-BC01-IND bulkhead coupler.

**Color-Coded to Avoid Misidentification That Can Cause Costly Downtime** This fiber cable features an aqua PVC jacket with LC duplex ends. The color-coding allows easy, fast OM3 identification in a crowded rack, patch panel or workstation and helps prevent the cable from becoming inadvertently disconnected.

## Specifications

| OVERVIEW   |              |
|------------|--------------|
| UPC Code   | 037332252746 |
| Technology | Multimode    |

### Highlights

- Protects 10Gb fiber Ethernet applications in outdoor or harsh environments
- Resists dust and endures immersion in 1.5 m of water up to 60 min.
- Low insertion loss of >0.10 db ensures a strong signal through your network
- Color-coded aqua for fast, easy OM3 identification in a crowded rack or patch panel

### Applications

- Connect 10G fiber Ethernet networks in factories, warehouses, recycling plants, machine shops and other environments prone to dust or water
- Provide connectivity in outdoor environments susceptible to rain, such as a stadium or outdoor arena

### Package Includes

- N820-05M-IND 10Gb Duplex Multimode 50/125 OM3 Fiber Patch Cable, Aqua, 5 m

|                                      |                              |
|--------------------------------------|------------------------------|
| Optical Mode                         | OM3                          |
| <b>PHYSICAL</b>                      |                              |
| Cable Jacket Color                   | Aqua                         |
| Connector Color                      | Beige                        |
| Cable Jacket Material                | PVC                          |
| Cable Jacket Rating                  | OFNR                         |
| Cable Outer Diameter (OD)            | 7.5 mm                       |
| Clad Diameter (microns)              | 50                           |
| Core Diameter (microns)              | 125                          |
| Number of Fibers                     | 2                            |
| Cable Length (ft.)                   | 16.4                         |
| Cable Length (m)                     | 5.00                         |
| Cable Length (in.)                   | 196.850                      |
| Cable Length (cm)                    | 500                          |
| Minimum Bend Radius                  | 7.5 * 20=150mm               |
| Fiber Cable Length                   | 5M (16.4 ft)                 |
| <b>ENVIRONMENTAL</b>                 |                              |
| Operating Temperature Range          | 14° to 122°F (-10° to 50°C)  |
| Storage Temperature Range            | 5° to 140°F (-15° to 60°C)   |
| Relative Humidity                    | 0% to 90% RH, Non-Condensing |
| Operating Humidity Range             | 0% to 90% RH, Non-Condensing |
| Storage Humidity Range               | 0% to 90% RH, Non-Condensing |
| <b>COMMUNICATIONS</b>                |                              |
| Network Compatibility                | 10 Gbps                      |
| Attenuation @ 1310NM                 | 1.5dB/km                     |
| Attenuation @ 850NM                  | 3.5 dB/km                    |
| Insertion Loss                       | 0.10 dB                      |
| <b>CONNECTIONS</b>                   |                              |
| Side A - Connector 1                 | LC DUPLEX (MALE)             |
| Side B - Connector 1                 | LC DUPLEX (MALE)             |
| Endface Polish                       | PC                           |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                              |

# TRIPP-LITE

by **EAT•N**

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

|                                     |                           |
|-------------------------------------|---------------------------|
| Push/Pull Tabs                      | No                        |
| Breakout                            | No                        |
| Trunk                               | No                        |
| Optical Port                        | LC                        |
| <b>STANDARDS &amp; COMPLIANCE</b>   |                           |
| Protection Rating                   | IP68                      |
| Product Compliance                  | RoHS; REACH               |
| <b>WARRANTY &amp; SUPPORT</b>       |                           |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

# TRIPP-LITE

by **EAT•N**

© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.