

16-Port 10/100/1000 Mbps 1U Rack-Mount/Desktop Gigabit Ethernet Unmanaged Switch, Metal Housing

MODEL NUMBER: NG16



Energy-efficient unmanaged switch sets up in seconds with no configuration required. Provides a Gigabit network connection for multiple devices. Ideal for home or small offices, workgroups and creative production environments.

Description

The NG16 16-Port 10/100/1000 Mbps 1U Rack-Mount/Desktop Gigabit Ethernet Unmanaged Switch adds 10/100/1000 Mbps Ethernet capacity to your home office, small office, workgroup or creative production environment. Share large bandwidth-intensive files, such as CAD drawings and videos, at Gigabit speeds, improving efficiency and cutting costly downtime.

This rack-mount/desktop switch features 16 twisted-pair RJ45 Gigabit Ethernet ports that support auto-negotiable 10/100/1000 Mbps and auto MDI/MDIX cross-over detection functions for convenient plug-and-play capability. No configuration is required, so you can have your Gigabit network up and running immediately. Easy-to-read LEDs indicate connection and activity status for each port. IEEE 802.3x flow control allows smooth transmission of large files.

The NG16 supports IEEE 802.3az Energy Efficient Ethernet standards by putting unused ports into a low-power state without interrupting network connections. It consumes very little input power—just seven watts max. The detachable five-foot input cord with NEMA 5-15P plug connects to a protected UPS, generator or mains input AC source. The heavy-duty metal housing is designed for desktop installation or mounting into 1U of an EIA-standard 19-inch rack with the included brackets.

Features

Unmanaged Network Switch for Home/Small Offices or Workgroups 16 twisted-pair RJ45 Gigabit Ethernet ports
Auto-negotiable 10/100/1000 Mbps
Automatic MDI/MDIX cross-over detection
32 Gbps switching capacity (2 Gbps per port with full duplex)
Easy-to-read LEDs indicate connection and activity status for each port
Supports 9k jumbo frames
Supports MAC address auto-learning and auto-aging
Supports 802.3x flow control (full duplex) and back pressure (half duplex)

Compliant with IEEE 802.3az Energy Efficient Ethernet Standards Automatically shifts unused ports to low-power state without interrupting network connection
Consumes very little input power—just 7W max
Also meets IEEE 802.3ab, 802.3i, 802.3u and 802.3 standards

Heavy-Duty Metal Housing Fanless design for silent operation
Detachable 5 ft. AC power cord with NEMA 5-15P plug
Plug-and-play—no configuration necessary

Versatile Installation Options Includes rubber feet for secure placement on flat desktop surface
Mounts in

Highlights

- 16 auto-negotiable 10/100/1000 Mbps RJ45 ports
- Supports auto MDI/MDIX cross-over function
- Consumes very little input power—just 7W max
- 2 Gbps switching capacity per port with full duplex
- Plug-and-play with no configuration required

Package Includes

- NG16 16-Port 10/100/1000 Mbps 1U Rack-Mount/Desktop Gigabit Ethernet Unmanaged Switch
- Detachable AC power cord with NEMA 5-15P plug, 5 ft.
- (2) Mounting brackets
- (8) Screws
- (4) Rubber feet
- Owner's manual

1U of EIA-standard 19 in. rack with included brackets
Grounding lug included

Works with the Most Popular Web Browsers

The NG16 is browser-based and works independently from the connected computer's operating system. Because switch compatibility is based on common hardware standards, rather than system software dependencies, the NG16 accommodates most platforms. Preferred web browsers include Google Chrome (on both Windows and macOS) and Microsoft Edge (Windows only).

Specifications

| OVERVIEW | |
|-----------------------------------|--|
| UPC Code | 037332194725 |
| Product Type | Unmanaged Switch |
| INPUT | |
| Electrical Consumption (Max) | 7W |
| Nominal Input Voltage Description | Accepts 100-240V AC nominal input |
| Plug Type | Includes NEMA 5-15P input plug |
| Voltage Compatibility (VAC) | 100-240 |
| Input Plug Type | NEMA 5-15P |
| Input Cord Length (ft.) | 5 |
| Input Cord Length (m) | 1.52 |
| POWER | |
| Power Consumption (Watts) | 7 |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | Power LED (Green for Power On); One LED per RJ45 port (Green indicates 10/100Mbps link; Amber indicates 1000Mbps link; LEDs flash to indicate port activity) |
| PHYSICAL | |
| Primary Form Factor | Desktop; Rackmount |
| Color | Black |
| Form Factors Supported | Desktop, Rackmount |
| Shipping Dimensions (hwd / in.) | 2.59 x 10.15 x 13.38 |
| Shipping Dimensions (hwd / cm) | 6.60 x 25.80 x 34.00 |
| Shipping Weight (lbs.) | 4.91 |
| Shipping Weight (kg) | 2.23 |
| Unit Dimensions (hwd / in.) | 4.960 x 11.023 x 1.730 |
| Unit Dimensions (hwd / cm) | 12.5 x 27.9 x 4.39 |

| | |
|--------------------------------------|---|
| Unit Weight (lbs.) | 3.2 |
| Unit Weight (kg) | 1.45 |
| Rack Units | 1 |
| ENVIRONMENTAL | |
| Storage Temperature Range | -40° to 158°F (-40° to 70°C) |
| Relative Humidity | 10 to 90% (non-condensing) |
| Operating Temperature | 32 to 104 F (0 to 40 C) |
| COMMUNICATIONS | |
| Network Compatibility | 1 Gbps (Gigabit) |
| Network Compatibility Details | Auto-negotiable |
| Switching Capacity | 32 Gbps |
| Switching Capacity Details | 2 Gbps per port with full duplex |
| CONNECTIONS | |
| Number of Ports | 16 |
| Ports | 16 |
| Ports Detail | 16x 10/100/1000BASE-T |
| SFP Uplink Ports | 0 |
| PoE Supported Ports | 0 |
| Network Switch Ports | (16) 10/100/1000 (RJ45) |
| FEATURES & SPECIFICATIONS | |
| Jumbo Frames | 10000 |
| Console Port | No |
| MAC Auto Learning | Yes |
| RMON | No |
| SNMP | No |
| Storm Control | No |
| DHCP Snooping | No |
| Auto MDI/MDIX Crossover Detection | Yes |
| Fans (Type/Quantity) | Fanless |
| STANDARDS & COMPLIANCE | |
| Product Compliance | IEEE 802.3 Auto-Negotiation; IEEE 802.3ab 1000Base-T; IEEE 802.3az (Energy Efficient Ethernet); IEEE 802.3i 10Base-T; IEEE 802.3u 100Base-TX/FX; IEEE 802.3x Flow Control |

WARRANTY & SUPPORT

Product Warranty Period
(Worldwide)

5-year limited warranty