

# NGTG15N60S1EG

## IGBT - Short-Circuit Rated

This Insulated Gate Bipolar Transistor (IGBT) features a robust and cost effective Non-Punch Through (NPT) Trench construction, and provides superior performance in demanding switching applications. Offering both low on state voltage and minimal switching loss, the IGBT is well suited for motor drive control and other hard switching applications.

### Features

- Low Saturation Voltage Resulting in Low Conduction Loss
- Low Switching Loss in Higher Frequency Applications
- 5  $\mu$ s Short Circuit Capability
- Excellent Current versus Package Size Performance Density
- This is a Pb-Free Device

### Typical Applications

- White Goods Appliance Motor Control
- General Purpose Inverter
- AC and DC Motor Control

### ABSOLUTE MAXIMUM RATINGS

| Rating   | Symbol    | Value       | Unit             |
|--|-----------|-------------|------------------|
| Collector-emitter voltage  | $V_{CES}$ | 650         | V                |
| Collector current<br>@ $T_C = 25^\circ\text{C}$<br>@ $T_C = 100^\circ\text{C}$                                   | $I_C$     | 30<br>15    | A                |
| Pulsed collector current, $T_{\text{pulse}}$ limited by $T_{J\text{max}}$  | $I_{CM}$  | 120         | A                |
| Gate-emitter voltage   | $V_{GE}$  | $\pm 20$    | V                |
| Power dissipation<br>@ $T_C = 25^\circ\text{C}$<br>@ $T_C = 100^\circ\text{C}$                                   | $P_D$     | 117<br>47   | W                |
| Short circuit withstand time<br>$V_{GE} = 15\text{ V}$ , $V_{CE} = 400\text{ V}$ , $T_J \leq +150^\circ\text{C}$ | $t_{SC}$  | 5           | $\mu\text{s}$    |
| Operating junction temperature range   | $T_J$     | -55 to +150 | $^\circ\text{C}$ |
| Storage temperature range  | $T_{stg}$ | -55 to +150 | $^\circ\text{C}$ |
| Lead temperature for soldering, 1/8" from case for 5 seconds   | $T_{SLD}$ | 260         | $^\circ\text{C}$ |



Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.



ON Semiconductor®


[www.onsemi.com](http://www.onsemi.com)

15 A, 650 V  
 $V_{CEsat} = 1.5\text{ V}$



TO-220  
CASE 221A  
STYLE 9

### MARKING DIAGRAM



A = Assembly Location  
Y = Year  
WW = Work Week  
G = Pb-Free Package

### ORDERING INFORMATION

| Device        | Package             | Shipping        |
|---------------|---------------------|-----------------|
| NGTG15N60S1EG | TO-220<br>(Pb-Free) | 50 Units / Rail |

# NGTG15N60S1EG

## THERMAL CHARACTERISTICS

| Rating  | Symbol          | Value | Unit                        |
|---|-----------------|-------|-----------------------------|
| Thermal resistance junction to case, for IGBT | $R_{\theta JC}$ | 1.06  | $^{\circ}\text{C}/\text{W}$ |
| Thermal resistance junction to ambient        | $R_{\theta JA}$ | 60    | $^{\circ}\text{C}/\text{W}$ |

## ELECTRICAL CHARACTERISTICS ( $T_J = 25^{\circ}\text{C}$ unless otherwise specified)

| Parameter | Test Conditions | Symbol | Min | Typ | Max | Unit |
|-----------|-----------------|--------|-----|-----|-----|------|
|-----------|-----------------|--------|-----|-----|-----|------|

### STATIC CHARACTERISTIC

|   |   |               |             |             |             |               |
|---|---|---------------|-------------|-------------|-------------|---------------|
| Collector-emitter breakdown voltage, gate-emitter short-circuited | $V_{GE} = 0 \text{ V}, I_C = 500 \mu\text{A}$   | $V_{(BR)CES}$ | 650         | -           | -           | V             |
| Collector-emitter saturation voltage                              | $V_{GE} = 15 \text{ V}, I_C = 15 \text{ A}$<br>$V_{GE} = 15 \text{ V}, I_C = 15 \text{ A}, T_J = 150^{\circ}\text{C}$       | $V_{CEsat}$   | 1.3<br>1.55 | 1.5<br>1.75 | 1.7<br>1.95 | V             |
| Gate-emitter threshold voltage                                    | $V_{GE} = V_{CE}, I_C = 250 \mu\text{A}$  | $V_{GE(th)}$  | 4.5         | 5.5         | 6.5         | V             |
| Collector-emitter cut-off current, gate-emitter short-circuited   | $V_{GE} = 0 \text{ V}, V_{CE} = 600 \text{ V}$<br>$V_{GE} = 0 \text{ V}, V_{CE} = 600 \text{ V}, T_J = 150^{\circ}\text{C}$ | $I_{CES}$     | -           | 10          | -<br>200    | $\mu\text{A}$ |
| Gate leakage current, collector-emitter short-circuited           | $V_{GE} = 20 \text{ V}, V_{CE} = 0 \text{ V}$   | $I_{GES}$     | -           | -           | 100         | nA            |
| Forward Transconductance  | $V_{CE} = 20 \text{ V}, I_C = 15 \text{ A}$   | $g_{fs}$      | -           | 10.1        | -           | S             |

### DYNAMIC CHARACTERISTIC

|                              |   |           |   |      |   |    |
|------------------------------|---|-----------|---|------|---|----|
| Input capacitance            | $V_{CE} = 20 \text{ V}, V_{GE} = 0 \text{ V}, f = 1 \text{ MHz}$    | $C_{ies}$ | - | 1950 | - | pF |
| Output capacitance           |   | $C_{oes}$ | - | 70   | - |    |
| Reverse transfer capacitance |   | $C_{res}$ | - | 48   | - |    |
| Gate charge total            | $V_{CE} = 480 \text{ V}, I_C = 15 \text{ A}, V_{GE} = 15 \text{ V}$ | $Q_g$     | - | 88   | - | nC |
| Gate to emitter charge       |   | $Q_{ge}$  | - | 16   | - |    |
| Gate to collector charge     |   | $Q_{gc}$  | - | 42   | - |    |

### SWITCHING CHARACTERISTIC , INDUCTIVE LOAD

|                         |   |              |   |       |   |    |
|-------------------------|---|--------------|---|-------|---|----|
| Turn-on delay time      | $T_J = 25^{\circ}\text{C}$<br>$V_{CC} = 400 \text{ V}, I_C = 15 \text{ A}$<br>$R_g = 22 \Omega$<br>$V_{GE} = 0 \text{ V} / 15 \text{ V}^*$  | $t_{d(on)}$  | - | 65    | - | ns |
| Rise time               |   | $t_r$        | - | 28    | - |    |
| Turn-off delay time     |   | $t_{d(off)}$ | - | 170   | - |    |
| Fall time               |   | $t_f$        | - | 140   | - |    |
| Turn-on switching loss  |   | $E_{on}$     | - | 0.550 | - | mJ |
| Turn-off switching loss |   | $E_{off}$    | - | 0.350 | - |    |
| Total switching loss    |   | $E_{ts}$     | - | 0.900 | - |    |
| Turn-on delay time      | $T_J = 150^{\circ}\text{C}$<br>$V_{CC} = 400 \text{ V}, I_C = 15 \text{ A}$<br>$R_g = 22 \Omega$<br>$V_{GE} = 0 \text{ V} / 15 \text{ V}^*$ | $t_{d(on)}$  | - | 65    | - | ns |
| Rise time               |   | $t_r$        | - | 28    | - |    |
| Turn-off delay time     |   | $t_{d(off)}$ | - | 180   | - |    |
| Fall time               |   | $t_f$        | - | 260   | - |    |
| Turn-on switching loss  |   | $E_{on}$     | - | 0.650 | - | mJ |
| Turn-off switching loss |   | $E_{off}$    | - | 0.600 | - |    |
| Total switching loss    |   | $E_{ts}$     | - | 1.250 | - |    |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

\*Includes diode reverse recovery loss using NGTB15N60S1EG.

# NGTG15N60S1EG

## TYPICAL CHARACTERISTICS




Figure 1. Output Characteristics




Figure 2. Output Characteristics




Figure 3. Output Characteristics




Figure 4. Typical Transfer Characteristics




Figure 5.  $V_{CE(sat)}$  vs.  $T_J$




Figure 6. Typical Capacitance

# NGTG15N60S1EG

## TYPICAL CHARACTERISTICS




Figure 7. Typical Gate Charge




Figure 8. Switching Loss vs. Temperature




Figure 9. Switching Time vs. Temperature




Figure 10. Switching Loss vs.  $I_C$




Figure 11. Switching Time vs.  $I_C$




Figure 12. Switching Time vs.  $R_G$

# NGTG15N60S1EG

## TYPICAL CHARACTERISTICS




Figure 13. Switching Time vs.  $R_G$




Figure 14. Switching Loss vs.  $V_{CE}$




Figure 15. Switching Time vs.  $V_{CE}$




Figure 16. Safe Operating Area




Figure 17. Reverse Bias Safe Operating Area

# NGTG15N60S1EG

## TYPICAL CHARACTERISTICS




Figure 18. IGBT Transient Thermal Impedance




Figure 19. Test Circuit for Switching Characteristics

# NGTG15N60S1EG



Figure 20. Definition of Turn On Waveform



Figure 21. Definition of Turn Off Waveform



**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at [www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)