



ELECTRONICS, INC.
 44 FARRAND STREET
 BLOOMFIELD, NJ 07003
 (973) 748-5089
<http://www.nteinc.com>

NTE30092 Light Emitting Diode (LED) Yellow + Green SOT-23 Surface Mount

Features:

- 3.0mm x 1.6mm SOT-23 SMT LED, 1.0mm Thickness
- Yellow + Green
- Common Anode Pin Configuration

Absolute Maximum Ratings: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

DC Forward Current, I_F	25mA
Peak Forward Current (Note 1), $I_{F(\text{peak})}$	50mA
Reverse Voltage, V_R	5V
Power Dissipation, P_D	
Yellow	90mW
Green	84mW
Operating Temperature Range, T_{opr}	-30° to $+85^\circ\text{C}$
Storage Temperature Range, T_{stg}	-40° to $+85^\circ\text{C}$
Reflow Soldering (Preheat $+150^\circ$ to $+180^\circ\text{C}$ 60sec to 120sec, 10sec max)	$+260^\circ\text{C}$

Note 1. 1/10 Duty Cycle, 0.1ms Pulse Width.

Electrical/Optical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Viewing Angle of Half Power	$2\theta_{1/2}$	$I_F = 20\text{mA}$	-	140	-	degrees
Luminous Intensity	I_V	$I_F = 20\text{mA}$, Note 2				
Yellow			2.0	4.0	-	mcd
Green			2.0	4.0	-	mcd
Forward Voltage	V_F	$I_F = 20\text{mA}$				
Yellow			-	2.10	2.80	V
Green			-	2.15	2.80	V
Peak Emission Wave Length	λ_P	$I_F = 20\text{mA}$				
Yellow			-	589	-	nm
Green			-	570	-	nm
Dominant Wavelength	λ_d (HUE)	$I_F = 20\text{mA}$, Note 3				
Yellow			-	585	-	nm
Green			-	567	-	nm

Note 2. Tolerance: 30% measured with EXELTRON 2001

Note 3. The dominant wavelength, λ_d , is derived from the CIE Chromatic Diagram and represents the color of the device.



