

## VGA Easy Pull High-Resolution RGB Coaxial Cable (HD15 M/M), 100 ft. (30.5 m)

MODEL NUMBER: P503-100



### Highlights

- Two-piece design runs through conduit or other tight areas
- Threaded circular DIN connector provides secure reattachment
- Superior-molded cables with foil and braid shielding for maximum EMI/RFI protection

### Package Includes

- 100-ft. (30.5 m) Male/Male Easy Pull SVGA/VGA Monitor Cable w/ Connectors

### Description

Tripp Lite's 100-ft. (30.5 m) SVGA/VGA Easy Pull Monitor Cable with Connectors makes running long length video cables a snap. The pull-apart design allows the cable to be run through conduit or other tight areas that a HD15 connector wouldn't fit through. Diameter of the circular DIN end is only 7/8". Circular Easy Pull connector is threaded to ensure maximum security once the cable is reattached. The mini-coax (RGB) and paired video wire construction delivers superior signal quality. Double shielding (foil and braid) provides maximum EMI/RFI protection. Both high density DB15 males are molded and have integral strain relief to ensure they last a long time.

### Features

- Two-piece design runs through conduit or other tight areas
- Threaded circular DIN connector provides secure reattachment
- Superior-molded cables with foil and braid shielding for maximum EMI/RFI protection
- RGB 75-ohm coax construction for maximum video resolution
- HD15 male to HD15 male molded connectors
- Supports resolutions up to 1600 x 1200

## Specifications

| OVERVIEW     |                |
|--------------|----------------|
| UPC Code     | 037332142276   |
| Product Type | Passive Cable  |
| Technology   | Coax; VGA/SVGA |
| Cable Type   | Passive        |
| PHYSICAL     |                |

|                                      |                           |
|--------------------------------------|---------------------------|
| Color                                | Black                     |
| Cable Jacket Color                   | Black                     |
| Cable Length (ft.)                   | 100                       |
| Cable Length (m)                     | 30.49                     |
| Cable Length (in.)                   | 1200                      |
| Shipping Dimensions (hwd / in.)      | 17.00 x 14.00 x 1.00      |
| Shipping Dimensions (hwd / cm)       | 43.18 x 35.56 x 2.54      |
| Shipping Weight (lbs.)               | 7.60                      |
| Shipping Weight (kg)                 | 3.45                      |
| <b>CONNECTIONS</b>                   |                           |
| Side A - Connector 1                 | HD15 (MALE)               |
| Side B - Connector 1                 | HD15 (MALE)               |
| Latching or Gripping Connector       | No                        |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                           |
| IP68 Rated                           | No                        |
| IP20 Rated                           | No                        |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                           |
| Product Compliance                   | RoHS; EIA/ECA-310-E       |
| <b>WARRANTY &amp; SUPPORT</b>        |                           |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty |