

SERIES: P78-2000-S | **DESCRIPTION:** NON-ISOLATED SWITCHING REGULATOR

FEATURES


- 2 A of output current
- high efficiency up to 95%
- no-load input current as low as 0.1 mA
- wide temperature range: -40°C ~ +85°C
- output short circuit protection
- pin-out compatible with linear regulators
- designed to meet EN/BS EN 62368



MODEL	input voltage		output voltage	output current	output power	ripple and noise ^{1,2}	efficiency
	typ (Vdc)	range (Vdc)	(Vdc)	max (mA)	max (W)	max (mVp-p)	typ (%)
P78X2-2000-S	24	4.5~28	1.8	2000	3.6	75	83
P7802-2000-S	24	4.5~36	2.5	2000	5	75	89
	12	8~32	-2.5	1000	-2.5	150	84
P7803-2000-S	24	6~36	3.3	2000	6.6	75	89
	12	8~31	-3.3	1000	-3.3	150	83
P7805-2000-S	24	8~36	5	2000	10	75	92
	12	8~30	-5	1000	-5	150	84
P7806-2000-S	24	10~36	6.5	2000	13	75	92
	12	8~29	-6.5	1000	-6.5	150	85
P7809-2000-S	24	13~36	9	2000	18	75	95
	12	8~26	-9	1000	-9	150	84
P7812-2000-S	24	16~36	12	2000	24	75	96
	12	8~23	-12	1000	-12	150	85
P7815-2000-S	24	18~36	15	2000	30	75	96
	12	8~20	-15	1000	-15	150	85

Notes: 1. Ripple and noise are measured at 20 MHz BW, nominal input, full load by "parallel cable" method with 1 µF ceramic and 10 µF electrolytic capacitors on the output.
2. 20~100% load ripple & noise ≤ 100 mVp-p. 0~20% load ripple & noise ≤ 180 mVp-p

PART NUMBER KEY



INPUT

parameter	conditions/description	min	typ	max	units
operating input voltage	1.8 Vdc output model	4.5	24	28	Vdc
	2.5 Vdc output model	4.5	24	36	Vdc
	3.3 Vdc output model	6	24	36	Vdc
	5.0 Vdc output model	8	24	36	Vdc
	6.5 Vdc output model	10	24	36	Vdc
	9 Vdc output model	13	24	36	Vdc
	12 Vdc output model	16	24	36	Vdc
no load input current	positive output, nominal Vin	1.8 & 2.5 Vdc output all other outputs		0.2 0.1	mA mA
	negative output, nominal Vin	-2.5, -3.3, -5, -6.5 Vdc output all other outputs		1 2	mA mA
filter	capacitance filter				

OUTPUT

parameter	conditions/description	min	typ	max	units
capacitive load	1.8 & 2.5 Vdc output models			2000	μF
	3.3 Vdc output model			1800	μF
	5 & 6.5 Vdc output models			1000	μF
	9 Vdc output model			680	μF
	12 & 15 Vdc output models			470	μF
line regulation	input voltage range, full load		±0.4	±0.8	%
load regulation	from 10% to 100% load		±0.5	±1.5	%
voltage accuracy	100% load, input voltage range				
	1.8, 2.5, 3.3 Vdc output models all other models		±2 ±2	±4 ±3	% %
switching frequency	100% load, nominal input				
	5 Vdc output model			200	kHz
	12 Vdc output model			270	kHz
	15 Vdc output model			300	kHz
transient recovery time	25% load step change		0.2	1	mS
	25% load step change				
transient response deviation	1.8 & 2.5 Vdc output models		80	150	mV
	positive output: all other models		50	150	mV
	negative output: all other models		100	150	mV
temperature coefficient	-40°C ~ 85°C			±0.03	%/°C

PROTECTIONS

parameter	conditions/description	min	typ	max	units
short circuit protection	continuous, automatic recovery				

SAFETY AND COMPLIANCE

parameter	conditions/description	min	typ	max	units
safeties approval	designed to meet 62368: EN, BS EN				
conducted emissions	CISPR32/EN55032 class B (see fig. 4-② for recommended circuit)				
radiated emissions	CISPR32/EN55032 class B (see fig. 4-② for recommended circuit)				
ESD	IEC/EN 61000-4-2, contact ± 6kV, perf. Criteria B				
radiated immunity	IEC/EN 61000-4-3, 10V/m, perf. Criteria A				
EFT/burst	IEC/EN 61000-4-4, ± 1kV (see fig. 4-① for recommended circuit), perf. Criteria B				
surge	IEC/EN 61000-4-5, line to line ± 1kV (see fig. 4-① for recommended circuit), perf. Criteria B				
conducted immunity	IEC/EN 61000-4-6, 3 Vr.ms, perf. Criteria A				

SAFETY AND COMPLIANCE

parameter	conditions/description	min	typ	max	units
MTBF	as per MIL-HDBK-217F @ 25°C	2,000			K hours
RoHS	2011/65/EU				

ENVIRONMENTAL

parameter	conditions/description	min	typ	max	units
operating temperature	see derating curve	-40		85	°C
storage temperature		-55		125	°C
storage humidity	non-condensing	5		95	%

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
hand soldering	1.5mm from case for 10 seconds			260	°C



MECHANICAL

parameter	conditions/description	min	typ	max	units
dimensions	11.50 x 9.00 x 17.50 (0.453 x 0.354 x 0.689 inch)				mm
case material	Black flame-retardant and heat-resistant plastic (UL94-V0)				
weight			3.8		g

MECHANICAL DRAWING

units: mm [inches]
 tolerance: ± 0.25 [± 0.010]
 pin section tolerance: ± 0.10 [± 0.004]


PIN CONNECTIONS		
Pin	Function (positive output)	Function (negative output)
1	+Vin	+Vin
2	GND	-Vo
3	+Vo	GND



Note : Grid 2.54*2.54mm


DERATING CURVES

Figure 1




EFFICIENCY CURVES


**EFFICIENCY VS INPUT LOAD
P7805-2000-S (full load)**




**EFFICIENCY VS OUTPUT LOAD
P7805-2000-S (Vin = 24 V)**



**EFFICIENCY VS INPUT LOAD
P7815-2000-S (full load)**




**EFFICIENCY VS OUTPUT LOAD
P7815-2000-S (Vin = 24 V)**




TYPICAL APPLICATION CIRCUIT

**Figure 2
positive output**



**Figure 2
negative output**



- Note:
1. C1 and C2 are required and should be connected close to the pin terminal of the module.
 2. The capacitance of C1 and C2 refer to Sheet 1.
 3. To reduce the output ripple further, C2 can be increased properly if required, tantalum capacitor and aluminum electrolytic capacitor of low ESR may also suffice.
 4. Cannot be used in parallel to enlarge the power for output and hot swap.

Table 1

Part No.	C1 (ceramic capacitor)	C2 (ceramic capacitor)
P78X2-2000-S	22 μ F/50V	22 μ F/10V
P7802-2000-S	22 μ F/50V	22 μ F/10V
P7803-2000-S	22 μ F/50V	22 μ F/10V
P7805-2000-S	22 μ F/50V	22 μ F/10V
P7806-2000-S	22 μ F/50V	22 μ F/10V
P7809-2000-S	22 μ F/50V	22 μ F/16V
P7812-2000-S	22 μ F/50V	22 μ F/25V
P7815-2000-S	22 μ F/50V	22 μ F/25V

EMC RECOMMENDED CIRCUIT

Figure 3




Table 2

Recommended external circuit components	
FUSE	choose according to practical input current
C0	100 μ F /100V
LDM1	22 μ H
C4	680 μ F /50V
C1/C2	10 μ F /50V
C3	22 μ F/25V

- Note: Part ① in the Fig. 4 is for EMS test, part ② is for EMI filtering; parts ① and ② can be added based on actual requirement.

REVISION HISTORY

rev.	description	date
1.0	initial release	01/22/2020
1.01	logo update	02/21/2020
1.02	derating curve, efficiency curves and circuit figures updated	09/23/2021
1.03	datasheet updated	05/24/2022
1.04	CE certification removed	11/02/2022
1.05	1.8V, 2.5V & 6.5V input model added	09/22/2023

The revision history provided is for informational purposes only and is believed to be accurate.



Headquarters
20050 SW 112th Ave.
Tualatin, OR 97062
800.275.4899

Fax 503.612.2383
cui.com
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.