


**SERIES:** PDQE30-D | **DESCRIPTION:** DC-DC CONVERTER

**FEATURES**


- 30W isolated output
- 1500 Vdc isolation
- 1 x 1 inch industry standard package
- ultra-wide 4:1 input voltage range
- EN62368 approved
- wide temperature range: -40°C to +85°C
- high efficiency up to 88%
- input under-voltage protection, output short circuit, over-current, over-voltage protection



| MODEL            | input voltage |                | output voltage<br>(Vdc) | output current |             | output power<br>(W) | ripple and noise <sup>1</sup><br>(mVp-p) | efficiency<br>(%) |
|------------------|---------------|----------------|-------------------------|----------------|-------------|---------------------|--|-------------------|
|                  | typ<br>(Vdc)  | range<br>(Vdc) |                         | min<br>(mA)    | max<br>(mA) |                     |  |                   |
| PDQE30-Q48-S5-D  | 48            | 18~75          | 5                       | 0              | 6000        | 30                  | 120                                      | 88                |
| PDQE30-Q48-S12-D | 48            | 18~75          | 12                      | 0              | 2500        | 30                  | 120                                      | 88                |
| PDQE30-Q48-S15-D | 48            | 18~75          | 15                      | 0              | 2000        | 30                  | 120                                      | 88                |
| PDQE30-Q48-S24-D | 48            | 18~75          | 24                      | 0              | 1250        | 30                  | 150                                      | 88                |

Note: 1. Ripple & noise testing condition at nominal input voltage and 5%-100% load, 20MHz bandwidth

**PART NUMBER KEY**



## INPUT

| parameter             | conditions/description                    | min  | typ   | max    | units |
|-----------------------|---|------|-------|--------|-------|
| input voltage         |   | 18   | 48    | 75     | Vdc   |
| start-up voltage      | nominal input voltage                     |      |       | 18     | Vdc   |
| surge voltage         | nominal input voltage                     | -0.7 |       | 100    | Vdc   |
| filter                | capacitance filter                        |      |       |        |       |
| current               | nominal input voltage (full load/no load) |      | 710/8 | 735/15 | mA    |
| under-voltage lockout |   | 12   | 15.5  |        | Vdc   |
| start-up time         | nominal input voltage                     |      | 10    |        | mS    |
| CTRL <sup>1</sup>     | module on - open or pulled high           | 3.5  |       | 12     | Vdc   |
|                       | module off - pulled low to GND            | 0    |       | 1.2    | Vdc   |
|                       | input current when off                    |      | 2     | 7      | mA    |

Note: 1. CTRL is referenced to GND

## OUTPUT

| parameter               | conditions/description | min | typ  | max   | units |
|-------------------------|------------------------|-----|------|-------|-------|
| line regulation         | min to max Vin         |     | ±0.2 | ±0.5  | %     |
| load regulation         | 5% ~ 100% load         |     | ±0.5 | ±1    | %     |
| set-point accuracy      |                        |     | ±1   | ±3    | %     |
| switching frequency     | PWM mode               |     | 270  |       | kHz   |
| transient response      | 25% load step change   |     | ±3   | ±8    | %     |
|                         | 5V output              |     | ±3   | ±5    | %     |
|                         | others                 |     |      |       |       |
| temperature coefficient | full load              |     |      | ±0.03 | %/°C  |
| adjustability           | via trim pin           |     | ±10  |       | %     |

## PROTECTIONS

| parameter                | conditions/description    | min | typ | max | units |
|--------------------------|---------------------------|-----|-----|-----|-------|
| over voltage protection  |                           | 110 |     | 160 | %Vo   |
| over current protection  |                           | 110 |     | 260 | %Io   |
| short circuit protection | continuous, self-recovery |     |     |     |       |

## SAFETY AND COMPLIANCE

| parameter             | conditions/description   | min  | typ  | max | units  |
|-----------------------|--|------|------|-----|--------|
| isolation voltage     | input-output electric strength test for 1 minute                               | 1500 |      |     | Vdc    |
| isolation resistance  | input-output insulation at 500 Vdc   | 1000 |      |     | MΩ     |
| isolation capacitance | input-output capacitance at 100 KHz / 0.1 V                                    |      | 2000 |     | pF     |
| safety approvals      | EN62368 approved   |      |      |     |        |
| EMC                   | CISPR32/EN55032 Class B (see recommended circuit)                              |      |      |     |        |
| ESD                   | IEC/EN61000-4-2, Contact ±6K, perf. Criteria B                                 |      |      |     |        |
| radiated immunity     | IEC/EN61000-4-3, 10 v/m, perf. Criteria B                                      |      |      |     |        |
| EFT/burst             | IEC/EN61000-4-4, ±2KV, perf. Criteria B (see recommended circuit)              |      |      |     |        |
| surge                 | IEC/EN61000-4-5, line to line ±2KV, perf. Criteria B (see recommended circuit) |      |      |     |        |
| conducted immunity    | IEC/EN61000-4-6 3 Vrms, perf. Criteria B                                       |      |      |     |        |
| RoHS                  | yes  |      |      |     |        |
| MTBF                  | MIL-HDBK-217F @ 25°C   | 1000 |      |     | kHours |

## ENVIRONMENTAL


| parameter             | conditions/description | min | typ | max | units |
|-----------------------|------------------------|-----|-----|-----|-------|
| operating temperature |                        | -40 |     | 85  | °C    |
| storage temperature   |                        | -55 |     | 125 | °C    |
| humidity              | non-condensing         | 5   |     | 95  | %     |

## SOLDERABILITY

| parameter      | conditions/description          | min | typ | max | units |
|----------------|---------------------------------|-----|-----|-----|-------|
| hand soldering | 1.5 mm from case for 10 seconds |     |     | 300 | °C    |

## DERATING CURVES

Figure 1



Note:



## MECHANICAL

| parameter     | conditions/description   | min | typ  | max | units |
|---------------|--------------------------|-----|------|-----|-------|
| dimensions    | 25.40 × 25.40 × 11.70 mm |     |      |     | inch  |
| case material | aluminum alloy           |     |      |     |       |
| weight        |                          |     | 18.4 |     | g     |

## MECHANICAL DRAWING

units: inches [mm]  
tolerance: ± 0.50 [±0.020]


| PIN CONNECTIONS |          |
|-----------------|----------|
| PIN             | FUNCTION |
| 1               | Ctrl     |
| 2               | GND      |
| 3               | Vin      |
| 4               | Vo       |
| 5               | Trim     |
| 6               | 0V       |



Note: Grid 2.54\*2.54mm

## TYPICAL APPLICATION CIRCUIT


Figure 2



| Vout (Vdc) | Cin (μF) | Cout (μF) |
|------------|----------|-----------|
| 5/12/15    | 100      | 100       |
| 24         |          | 47        |

## EMC COMPLIANCE CIRCUITS

Figure 3




Note: We use Part ① in Fig. 3 for Immunity tests and Part ② for Emissions test. Selecting based on needs.

|          |  |
|----------|--|
| Model    | Vin: 48 V                                |
| FUSE     | Choose according to actual input current |
| C0, C4   | 470μF/100V                               |
| C1       | 10μF/100V                                |
| LDM1     | 22uH/3A                                  |
| C2       | 22uF/100V                                |
| LCM1     | 1.4mH/3A                                 |
| C3       | 22uF/100V                                |
| C5       | Refer to the Cout Fig.2                  |
| CY1, CY2 | 1nF/2KV                                  |


## TRIM FUNCTION FOR OUTPUT VOLTAGE ADJUSTMENT

Trim up



Trim resistor connection (dashed line shows internal resistor network).

Trim down



$$R_{TRIM} = \frac{a \cdot R_{BOTTOM}}{R_{BOTTOM} - a} - R_O \quad a = \frac{V_{REF}}{V_{OUT} - V_{REF}} \cdot R_{TOP}$$

Formula for Trim up

$$R_{TRIM} = \frac{a \cdot R_{TOP}}{R_{TOP} - a} - R_O \quad a = \frac{V_{OUT} - V_{REF}}{V_{REF}} \cdot R_{BOTTOM}$$

Formula for Trim down

| $V_{NOM}$<br>(Vdc) | $R_{TOP}$<br>(kΩ) | $R_{BOTTOM}$<br>(kΩ) | $R_O$<br>(kΩ) | $V_{REF}$<br>(V) |
|--------------------|-------------------|----------------------|---------------|------------------|
| 5                  | 8.832             | 2.87                 | 10            | 1.24             |
| 12                 | 11.00             | 2.87                 | 8.2           | 2.5              |
| 15                 | 14.40             | 2.87                 | 10            | 2.5              |
| 24                 | 24.87             | 2.87                 | 7.5           | 2.5              |

Note: Value for  $R_{TOP}$ ,  $R_{BOTTOM}$ ,  $R_O$ , and  $V_{REF}$  refer to Table 4 (fixed internal values).  
 $R_{TRIM}$ : Trim resistance  
 a: User-defined parameter, no actual meanings  
 $V_{NOM}$ : Nominal output voltage  
 $V_{OUT}$ : Target output voltage

## REVISION HISTORY

| rev. | description                                | date       |
|------|--|------------|
| 1.0  | initial release                            | 03/28/2020 |
| 1.01 | derating curve and circuit figures updated | 08/24/2021 |
| 1.02 | adjustability limits added                 | 03/14/2022 |
| 1.03 | output voltage trimming updated            | 05/23/2023 |

The revision history provided is for informational purposes only and is believed to be accurate.



**Headquarters**  
20050 SW 112th Ave.  
Tualatin, OR 97062  
**800.275.4899**

Fax 503.612.2383  
**cui.com**  
techsupport@cui.com

CUI offers a two (2) year limited warranty. Complete warranty information is listed on our website.

CUI reserves the right to make changes to the product at any time without notice. Information provided by CUI is believed to be accurate and reliable. However, no responsibility is assumed by CUI for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

CUI products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.