

Lantern Fronted Test Lead Set

Features

- Compatible with All Industry Standard 4mm Instrument Sockets
- 48" (1.2m) Double Insulated, Bi-Color Silicone Cable Boasts 250+ Copper Strands for Maximum Flexibility and Overall Performance
- Bi-Color Insulation Design Alerts User if Exposed Conductor Shock Hazard is Imminent
- Industry Standard 4mm Lantern Tip Accepts Push-On Accessories

NTE Type No.	Set Contains
72-090	1 Pair (Red & Black) of 48" (1.2m) Double Insulated Silicone Leads. Each lead is terminated by a 4mm Lantern Probe Tip on one end, the other end is terminated in a Right Angle Plug 1 Pair (Red & Black) of 1kV large Crocodile Clips



Specifications

IEC 1010 Rating: 1000V CAT3 20 Amps
 Temperature Rating: -10° to +150°C

OEM Fixed Tip Fused Probe Set

Features

- UL/CSA Compliant
- 48" (1.2m) Double Insulated, Bi-Color Silicone Cable Boasts 250+ Copper Strands for Maximum Flexibility and Overall Performance
- Compatible with All Industry Standard 4mm Instrument Sockets

NTE Type No.	Set Contains
72-078	1 Pair (Red & Black) of Double Insulated Silicone Lead Assemblies with Right Angle Plug



Specifications

IEC 1010 Rating: 1000V CAT3 / 600V CAT4
 Temperature Rating: -10° to +150°C
 Fuse Rating: 500mA/1000V 50kA

Accessories

Replacement Fuse: 72-002
 Compatible Crocodile Clips: 72-059 (Black), 72-060 (Red)

Multi-Stacking Safety Patch Cords

Features

- Compatible with All Industry Standard 4mm Banana Plugs and Sockets
- 48" (1.2m) Double Insulated, Bi-Color Silicone Cable Boasts 250+ Copper Strands for Maximum Flexibility and Overall Performance

NTE Type No.	Description
72-093	1 Pair (Red & Black) of Double Insulated Silicone Lead Assemblies with Stackable Plug



Specifications

IEC 1010 Rating: 1000V CAT3 / 600V CAT4 20 Amps