TE Internal #: 1-1337445-0

BNC RF Interface, Jack, 50 Ω , Bayonet, 4 GHz Operating

Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Board

Mount

View on TE.com >



Connectors > RF Connectors > Coax Connectors











RF Interface: BNC

RF Connector Style: Jack

RF Connector Mated Outer Diameter (Approximate): 14.53 mm [.572 in]

Impedance: 50Ω

RF Connector Coupling Mechanism: Bayonet

Features

Product Type Features

ar
oard
cuit Board

Configuration Features

PCB Mount Orientation	Vertical
Number of Positions	1
Number of Coaxial Contacts	1

Electrical Characteristics

Impedance	50 Ω
-----------	------

Body Features

Body Material	Brass	



Body Plating Material	Silver
Contact Features	
RF Connector Center Contact Plating Material	Silver
RF Connector Center Contact Material	Brass
Termination Features	
Termination Post & Tail Length	4 mm[.157 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
PCB Mount Retention	With
RF Connector Coupling Mechanism	Bayonet
Connector Mounting Type	Board Mount
RF Contact Captivation Method	Mechanical
Detent	With
Dimensions	
Mounting Post Length	4.5 mm[.177 in]
Profile Height from PCB	13 mm[.511 in]
RF Connector Mated Outer Diameter (Approximate)	14.53 mm[.572 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	-65 – 165 °C[-85 – 329 °F]
Operation/Application	
Operating Frequency	4 GHz
Packaging Features	
Packaging Quantity	50
Packaging Method	Bag
Other	
Grade	Professional
Dielectric Material	PTFE

Product Compliance

For compliance documentation, visit the product page on TE.com>



EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (3.32% in Component Part) Article Safe Usage Statements: Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts















Customers Also Bought





IBRIDGE VE 04 SMT 105 1 TO-C J 3

109900

TE Part #225822-E
POWELM GEWINK VOLLM M4 5 2,54
* EP 14 NI







TE Part #384268-E STVB/2 16 M AB 0374 4-00 0606 * 8360 247

TE Part #GA10K3CG1267 CHPC-TAIWAN GOLD CHIP

TE Part #GA10K3CG409 CHPC-TAIWAN GOLD CHIP

Documents

Product Drawings

BNC Str PCB Skt 50Ohm Silver P

English

CAD Files

3D PDF

English

Customer View Model

ENG_CVM_1-1337445-0_C.3d_igs.zip

English

Customer View Model

ENG_CVM_1-1337445-0_C.3d_stp.zip

English

Customer View Model

ENG_CVM_1-1337445-0_C.2d_dxf.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

BNC RF Interface, Jack, 50 Ω , Bayonet, 4 GHz Operating Frequency, Cable-to-Board, 1 Position, Printed Circuit Board, Board Mount



Product Specifications

Product Specification

English