KUP-14D11-24 - ACTIVE

Potter & Brumfield | Potter & Brumfield KUP

TE Internal #: 1-1393118-0 Power Relays, Industrial Panel Plug-In, Monostable, DC, 1250 mW Coil Power Rating DC, 472 Ω Coil Resistance, Potter & Brumfield KUP

View on TE.com >



Relays, Contactors & Switches > Relays > Power Relays



Power Relay Type: Industrial Panel Plug-In

Coil Magnetic System: Monostable, DC

Coil Power Rating DC: 1250 mW

Coil Resistance: 472 Ω

Coil Special Features: UL Coil Insulation Class B

Features

Product Type Features

Power Relay Type

Industrial Panel Plug-In

Electrical Characteristics

Insulation Initial Dielectric Between Coil & Contact Class

1500 – 2500 V

Actuating System DC	
Insulation Initial Dielectric Between Open Contacts 1200	00 Vrms
Contact Limiting Making Current 5 A	Λ
Contact Limiting Short-Time Current 5 A	Λ
Contact Limiting Continuous Current 5 A	Λ
Coil Power Rating Class 1000	00 – 1500 mW
Insulation Initial Dielectric Between Adjacent Contacts 2200	00 Vrms
Insulation Initial Resistance 100	Ο ΜΩ
Contact Limiting Breaking Current 5 A	Λ
Coil Magnetic System Mor	onostable, DC
Coil Power Rating DC 1250	50 mW
Coil Resistance 472	2 Ω
Coil Special Features UL C	Coil Insulation Class B
Coil Voltage Rating 24 V	VDC

& For support call+1 800 522 6752

09/18/2023 06:55PM | Page 1

Power Relays, Industrial Panel Plug-In, Monostable, DC, 1250 mW Coil Power Rating DC, 472 Ω Coil Resistance, Potter & Brumfield KUP



5 g[2.988 oz] Form C (CO) – 10 A, 16 A D A g			
5 g[2.988 oz] Form C (CO) – 10 A, 16 A D A g			
Form C (CO) – 10 A, 16 A O A g			
Form C (CO) – 10 A, 16 A O A g			
– 10 A, 16 A D A g			
Contact Switching Load (Min) 300m A @ 12V Contact Voltage Rating 240 VAC Body Features 240 VAC Product Weight 85 g[2.988 or] Contact Features Contact Features Contact Arrangement 3 I orm C (CO) Contact Current Class 5 – 10 A, 16 A Contact Current Class 5 – 10 A, 16 A Contact Material Ag Contact Material Ag Contact Material Ag Contact Number of Poles 3 Relay Terminal Type Ouick Connect, Solder Mechanical Attachment Vector Relay Mounting Type Socket Dimensions 10 – 50 mm Vectort Width 35 – 40 mm Product Width 35 – 40 mm Product Width 35 – 40 mm Width Class (Mechanical) 40 – 50 mm Width Class (Mechanical) 30 40 mm Product Width 35.7 mm[1.405 in] Product Width 38.9 mm[1.55 in] Product Height 38.9 mm[1.55 in] Product Height 30 – 70 °C Fenvironmental Ambient Temperature Class			
D A g			
g			
_			
Quick Connect, Solder			
uick Connect, Solder			
ocket			
5 – 40 mm			
0 – 50 mm			
0 – 40 mm			
35.7 mm[1.405 in]			
38.9 mm[1.55 in]			
0 mm[1.97 in]			
0 − 70 °C			
) °C[158 °F]			
5 – 70 °C			

Power Relays, Industrial Panel Plug-In, Monostable, DC, 1250 mW Coil Power Rating DC, 472 Ω Coil Resistance, Potter & Brumfield KUP



EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) SVHC > Threshold: Cadmium oxide (4.37% in Component Part) Aticle Safe Usage Statements Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts





Also in the Series | Potter & Brumfield KUP

C For support call+1 800 522 6752

Power Relays, Industrial Panel Plug-In, Monostable, DC, 1250 mW Coil Power Rating DC, 472 Ω Coil Resistance, Potter & Brumfield KUP





Customers Also Bought



KRPA-11AG-24=RELAY,GENPUR,	SMA Jack to SMA Jack Flange	D-603-1820-08	TOOL INS/REM	
OCTA				

Documents

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1393118-0_D.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1393118-0_D.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1393118-0_D.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

KUP Series Panel Plug-in Relay

English

Power Relays, Industrial Panel Plug-In, Monostable, DC, 1250 mW Coil Power Rating DC, 472 Ω Coil Resistance, Potter & Brumfield KUP



Product Specifications Definitions General Purpose Relays

English

Agency Approvals

UL

English