

#### Agastat

TE Internal #: 1-1423157-5

Time Delay Relays, Knob, 120 – 110 VAC Input, 10A@240VAC A, On-

Delay, 1 – 10 minutes Delay Time, Mounting Bracket

View on TE.com >



Relays, Contactors & Switches > Relays > Time Delay Relays



Type of Control: Knob

Time Delay Relay Input Voltage: 120 – 110 VAC

Time Delay Relay Contact Current Rating: 10A@240VAC A

Mode of Operation: On-Delay

Delay Time: 1 – 10 minutes

### **Features**

## **Product Type Features**

Product Type	Relay
Relay Type	Time Delay
Product Category	Electromechanical Relays
Magnetic Blow-Out Device	Without

## **Configuration Features**

Multiple Timing Ranges	Without

#### **Electrical Characteristics**

Actuating System	AC
Time Delay Relay Input Voltage	120 – 110 VAC

#### **Contact Features**

Contact Arrangement	2 Form C, DPDT, 2 C/O
Type of Control	Knob
Time Delay Relay Contact Current Rating	10A@240VAC A
Delay Time	1 – 10 minutes

## **Termination Features**

Termination Type	Screw Terminals
------------------	-----------------

#### **Mechanical Attachment**



Time Delay Relay Mounting Type	Mounting Bracket		
Dimensions			
Dimensions (L x W x H) (Approximate)	114.8 x 65.3 x 71.9 mm[4.523 x 2.572 x 2.832 in]		
Usage Conditions			
Operating Temperature Range	-30 – 75 °C		
Operation/Application			
Mode of Operation	On-Delay		
Other			
Repeatability (Max)	±10%		

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2022 (223) SVHC > Threshold: Not Yet Reviewed
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.



# **Compatible Parts**



# Customers Also Bought



















## **Documents**

CAD Files
3D PDF

3D

Customer View Model ENG\_CVM\_CVM\_1-1423157-5\_L.2d\_dxf.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1423157-5\_L.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1423157-5\_L.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

5-1773450-5\_sec12\_7000

English