# W51-A151A1-7 ✓ ACTIVE

TE Internal #: 1-1423673-6

Circuit Breakers, Thermal, Trip-Free - Switchable, Black, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 7A Current Rating, 1

Pole

View on TE.com >



Relays, Contactors & Switches > Circuit Breakers



Circuit Breaker Type: Thermal

Circuit Function: **Trip-Free - Switchable** 

Illuminated: No

Actuator Color: Black

Operating Voltage: 125 VAC

### **Features**

## **Product Type Features**

Circuit Breaker Style	Angular Button
Illumination Type	No Light
Actuator Type	Rocker
Terminal Configuration	6.35 [.25] Straight Quick Connect Tab
Circuit Breaker Type	Thermal
Illuminated	No

## **Configuration Features**

Panel Cutout Size	28.5 x 13.5 mm[1.122 x .531 in]
Circuit Function	Trip-Free - Switchable
Number of Poles	1

#### **Electrical Characteristics**

Operating Voltage	50 VDC
Current Rating	7 A
Interrupt Capacity	1000A @ 250VAC/50VDC

## **Body Features**

Actuator Color	Black	

## **Contact Features**

111p Time at 200%	Trip Time at 200%	4 – 40 seconds
-------------------	-------------------	----------------



#### Mechanical Attachment

Mounting Options	Snaps Into 1.122 x .531 (28.5 x 13.5) Panel Cutout
Dimensions	
Panel Thickness (Recommended)	.75 – 3 mm[.03 – .118 in]
Identification Marking	
Stamped Marking Type	RESET/OFF Printed

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**







TE Part # 1-14236/3-0 W51-A122B1-7=CKTBKR,THERM, ROCK

## Customers Also Bought





















TE Part #11028414-00 LDT1-028K W/TH LEADS/RIVE

## **Documents**

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-1423673-6\_E.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1423673-6\_E.3d\_igs.zip

English

Circuit Breakers, Thermal, Trip-Free - Switchable, Black, Operating Voltage 125 VAC, Operating Voltage 50 VDC, 7A Current Rating, 1 Pole



**Customer View Model** 

ENG\_CVM\_CVM\_1-1423673-6\_E.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

W51 Rocker-Actuated Thermal Circuit Breaker/Power Switch With Optional Indicator Lamp

English

**Agency Approvals** 

**CCC Certificate** 

English