

### Agastat

TE Internal #: 1-1437464-7

Time Delay Relays, Adjustable, 120 VAC Input, 125 VDC Input, 10A@120VAC A, Multiple Modes, Multiple Ranges Delay Time,

Socket

View on TE.com >



Relays, Contactors & Switches > Relays > Time Delay Relays



Type of Control: Adjustable

Time Delay Relay Input Voltage: 125 VDC

Time Delay Relay Contact Current Rating: 10A@120VAC A

Mode of Operation: Multiple Modes

## **Features**

## **Product Type Features**

Product Type	Relay
Relay Type	Time Delay
Product Category	Electromechanical Relays
Magnetic Blow-Out Device	Without
Configuration Features	
Status Indicator Type	LED
Multiple Timing Ranges	Without
Electrical Characteristics	
Actuating System	AC/DC
Time Delay Relay Input Voltage	125 VDC
Contact Features	
Contact Arrangement	2 Form C, DPDT, 2 C/O
Type of Control	Adjustable

# Termination Features

Delay Time

Time Delay Relay Contact Current Rating

10A@120VAC A

Multiple Ranges

### Mechanical Attachment



Time Delay Relay Mounting Type	Socket
Dimensions	
Dimensions (L x W x H) (Approximate)	72 x 36 x 90 mm[2.836 x 1.418 x 3.546 in]
Usage Conditions	
Operating Temperature Range	-30 – 65 °C
Operation/Application	
Mode of Operation	Multiple Modes
Other	
Repeatability (Max)	±1% ±10 msec
Comment	Does not include socket.

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach




## Compatible Parts



## Customers Also Bought




















## **Documents**

Product Drawings
SCFRX902AA=TIMER 10 AMPERES 12

English

Datasheets & Catalog Pages 5-1773450-5\_sec12\_SCF

English

## SCFRX902AA

Time Delay Relays, Adjustable, 120 VAC Input, 125 VDC Input, 10A@120VAC A, Multiple Modes, Multiple Ranges Delay Time, Socket

