B07D034BC2-0053 <

CII

TE Internal #: 1-1617004-0 Full-Size Relays, 2 Form C, DPDT, 2 C/O, Silver Cadmium Oxide, 26.5 VDC Input, 10 A, 26.5 VDC Coil Voltage, 300 Ω Coil Resistance View on TE.com >



Relays, Contactors & Switches > Relays > Mil-Aero Relays > Full-Size Relays



Full-Size Relay Contact Arrangement: 2 Form C, DPDT, 2 C/O

Contact Base Material: Silver Cadmium Oxide

Full-Size Relay Input Voltage: 26.5 VDC

Full-Size Relay Contact Current Rating: 10 A

Coil Voltage: 26.5 VDC

Features

Product Type Features

Enclosure Type	Hermetically Sealed	
Coil Latching	Without	
Product Type	Relay	

Relay Туре	Military/Aerospace High Performance	
MOSFET Driver	Without	
Configuration Features		
Transistor Driver	Without	
Electrical Characteristics		
Actuating System	DC	
Vibration	20G's, 10–2000Hz	
Coil Magnetic System	Non-Polarized, Monostable	
Shock	100G's, 6ms	
Coil Suppression Diode	Without	
Coil Polarity Protection Diode	Without	
Full-Size Relay Input Voltage	26.5 VDC	
Coil Voltage	26.5 VDC	
Full-Size Relay Coil Resistance	300 Ω	
Full-Size Relay Coil Power Rating (DC)	2340 mW	

B07D034BC2-0053

Full-Size Relays, 2 Form C, DPDT, 2 C/O, Silver Cadmium Oxide, 26.5 VDC Input, 10 A, 26.5 VDC Coil Voltage, 300 Ω Coil Resistance



Coil Power Measurement	Milliwatts
Full-Size Relay Contact Switching Voltage (Max)	28 VDC
Contact Features	
Full-Size Relay Contact Arrangement	2 Form C, DPDT, 2 C/O
Contact Base Material	Silver Cadmium Oxide
Full-Size Relay Contact Current Rating	10 A
Termination Features	
Termination Type	Socket Pins
Mechanical Attachment	
Full-Size Relay Mounting Type	Plain Case
Usage Conditions	
Operating Temperature Range	-65 – 125 °C
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Out of Scope

China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC	
Halogen Content	Not Yet Reviewed for halogen content	

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

B07D034BC2-0053

Full-Size Relays, 2 Form C, DPDT, 2 C/O, Silver Cadmium Oxide, 26.5 VDC Input, 10 A, 26.5 VDC Coil Voltage, 300 Ω Coil Resistance



Compatible Parts



Customers Also Bought



TE Part #1-1393771-6	TE Part #1-1393767-5	TE Part #326875	TE Part #F01667-000
JWD-171-24=REED RELAYS	R10-E2X2-V700=R10	TERMINAL,PIDG R 26-22 6	WP-191064-10-9

TE Part #7218310001 RPS-2.5K-18-12/2.0-S1-9

Documents

CAD Files

3D PDF

3D

Customer View Model ENG_CVM_CVM_1-1617004-0_T.2d_dxf.zip

English

Customer View Model

C For support call+1 800 522 6752

B07D034BC2-0053

Full-Size Relays, 2 Form C, DPDT, 2 C/O, Silver Cadmium Oxide, 26.5 VDC Input, 10 A, 26.5 VDC Coil Voltage, 300 Ω Coil Resistance



ENG_CVM_CVM_1-1617004-0_T.3d_igs.zip

English

Customer View Model ENG_CVM_CVM_1-1617004-0_T.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Datasheets & Catalog Pages 5-1773450-5_sec1_07

English

RELAY

English