

CGS | CGS SQ

TE Internal #: 1-1623778-1

220 Ω , Wire Wound, Power Resistor, 5 %, 48 x 12 x 8.5 mm, 2


Termination, Loose Piece - Box, 7 W, ±300 ppm/°C, Tinned Copper

Leads Termination, CGS SQ

View on TE.com >



Passive Components > Resistors > Through-Hole Resistors > Wirewound Resistor: Vertical Mount



Resistor Type: Power Resistor

Passive Component Dimensions: 48 x 12 x 8.5 mm

Number of Terminations: 2

Packaging Method: Loose Piece - Box
Passive Component Tolerance: 5 %

All Wirewound Resistor: Vertical Mount (202)

Features

Product Type Features

Product Type	Fixed Resistor			
Resistor Type	Power Resistor			
Element Type	Wire Wound			
Configuration Features				
Number of Resistors	1			
Electrical Characteristics				
Passive Component Tolerance	5 %			
Resistance Class	Up to $1k\Omega$			
Resistance Value	220 Ω			
Power Rating	7 W			
Body Features				

Passive Component Lead Type	Radial-Leaded

Termination Features

<u> </u>	Number of Terminations	2	

Passive Component Termination Material Type Tinned Copper Leads

Dimensions



Passive Component Dimensions	48 x 12 x 8.5 mm			
Usage Conditions				
Operating Temperature Range	-55 – 250 °C			
Temperature Coefficient	±300 ppm/°C			
Packaging Features				
Packaging Method	Loose Piece - Box			

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021 (211) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | CGS SQ



Customers Also Bought























220 Ω , Wire Wound, Power Resistor, 5 %, 48 x 12 x 8.5 mm, 2 Termination, Loose Piece - Box, 7 W, ± 300 ppm/°C, Tinned Copper Leads Termination, CGS SQ



Documents

Product Drawings SPS7 220R 5%

English

Datasheets & Catalog Pages

1309350_PASSIVE_COMPONENT

English

High Power Resistors - Type SQ Series

English

8-1773459-4_POWER_FILTERING_AND_RESISTIVE_SOLUTIONS_FOR_ELEVATORS_AND_ESCALATORS

English