# 1-1747414-3 ACTIVE

### Dynamic Series | Dynamic 4000 Series

TE Internal #: 1-1747414-3

Housing, Housing for Male Terminals, Wire-to-Wire, 3 Position, .25 in [6.35 mm] Centerline, Crimp, 1 Row, Black, Mating Retention,

Dynamic 4000 Series

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings > Receptacle and Tab Housing: 6.35 mm pitch, 600V











Connector Product Type: Housing

Connector & Housing Type: Housing for Male Terminals

Connector System: Wire-to-Wire

Number of Positions: 3

Centerline (Pitch): 6.35 mm [.25 in]

All Receptacle and Tab Housing: 6.35 mm pitch, 600V (27)

# **Features**

# **Product Type Features**

Connector Product Type	Housing
Connector & Housing Type	Housing for Male Terminals
Connector System	Wire-to-Wire
Sealable	No
Connector & Contact Terminates To	Wire & Cable

# **Configuration Features**

Number of Positions	3
Number of Rows	1

# **Body Features**

Primary Product Color	Black
· ······a.· y · · · · · · · · · · · · · · · · · ·	2.6.6.0

### **Termination Features**



Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Mating Retention	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	6.35 mm[.25 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts






# Also in the Series | Dynamic 4000 Series



PCB Connector Mounting(3)




PCB Headers & Receptacles(20)



PCB Terminal Blocks(2)



Wire-to-Board Connector Assemblies & Housings(29)



# Customers Also Bought



TE Part #2-353046-3
DYNAMIC D-5200S TAB HSG 3P K/Y



TE Part #353718-2 DYNAMIC D-3 TAB CONT. 3L AU 0.38 L/P



TE Part #1827587-2 DYNAMIC D1000 REC CONT M AU 0.38um L/P





TE Part #1-1747501-2 Contact: Component To Wire; 22-24A, 16-10 wire size



TE Part #176272-1 AMP UNIVERSAL POWER PLUG 3P



TE Part #170246-1
TYPE-3 1.57DIA PIN ASSY L/P

TE Part #170242-1
TYPE-3 1.57DIA PIN ASSY L/P



### **Documents**

### **Product Drawings**

DYNAMIC D4200 TAB HSG F/H 3P/X

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-1747414-3\_E.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1747414-3\_E.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1747414-3\_E.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

# Datasheets & Catalog Pages

1-1773732-4\_DYNAMIC\_SERIES\_CATALOG\_ENGLISH

Japanese

1-1773732-4\_DYNAMIC\_SERIES\_CATALOG\_ENGLISH

English

# **Product Specifications**

**Application Specification** 

English

# **Product Environmental Compliance**

**Product Compliance** 

English

**Product Compliance** 

English

### **Instruction Sheets**

Extraction Tool for Dynamic 4000 Series Connector

Japanese

Instruction Sheet (non U.S.)

Japanese

# **Agency Approvals**

**TUV Certificate** 

English