

#### Dynamic Series | Dynamic 1000 Series

TE Internal #: 1-1827581-1 PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 3.5 mm [. 137 in] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 1000 Series

#### View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > Header Assembly: Wire-to-Board, 5A, Gold Plated



Connector System: Wire-to-Board

Number of Positions: 3

Number of Rows: 3

Centerline (Pitch): 3.5 mm [.137 in ]

PCB Mount Orientation: Vertical

#### All Header Assembly: Wire-to-Board, 5A, Gold Plated (5)

# Features

### Product Type Features

| Connector System                  | Wire-to-Board         |  |  |  |  |
|-----------------------------------|-----------------------|--|--|--|--|
| Header Type                       | Fully Shrouded        |  |  |  |  |
| Sealable                          | No                    |  |  |  |  |
| Connector & Contact Terminates To | Printed Circuit Board |  |  |  |  |
| PCB Connector Assembly Type       | PCB Mount Header      |  |  |  |  |
| Configuration Features            |                       |  |  |  |  |
| Number of Positions               | 3                     |  |  |  |  |
| Number of Rows                    | 3                     |  |  |  |  |
| PCB Mount Orientation             | Vertical              |  |  |  |  |
| Body Features                     |                       |  |  |  |  |
| Primary Product Color             | Black                 |  |  |  |  |
| Contact Features                  |                       |  |  |  |  |
|                                   |                       |  |  |  |  |

PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 3.5 mm [.137 in] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 1000 Series



| Contact Mating Area Plating Material Thickness | .38 μm[15 μin]        |  |  |  |  |
|--|-----------------------|--|--|--|--|
| Contact Mating Area Plating Material           | Gold                  |  |  |  |  |
| Contact Type                                   | Pin                   |  |  |  |  |
| Contact Current Rating (Max)                   | 5 A                   |  |  |  |  |
| Termination Features                           |                       |  |  |  |  |
| Termination Method to Printed Circuit Board    | Through Hole - Solder |  |  |  |  |
| Mechanical Attachment                          |                       |  |  |  |  |
| Mating Alignment Type                          | Keyed                 |  |  |  |  |
| Mating Retention                               | With                  |  |  |  |  |
| PCB Mount Retention Type                       | Retention Leg         |  |  |  |  |
| Connector Mounting Type                        | Board Mount           |  |  |  |  |
| Mating Alignment                               | With                  |  |  |  |  |
| PCB Mount Alignment                            | Without               |  |  |  |  |
| PCB Mount Retention                            | With                  |  |  |  |  |
| Housing Features                               |                       |  |  |  |  |
| Housing Material                               | Polyester GF          |  |  |  |  |
| Centerline (Pitch)                             | 3.5 mm[.137 in]       |  |  |  |  |

# Usage Conditions

| Operating Temperature Range   | -55 – 105 °C[-67 – 221 °F]              |  |  |  |  |  |
|---|---|--|--|--|--|--|
| Operation/Application   |   |  |  |  |  |  |
| Circuit Application   | Power & Signal                          |  |  |  |  |  |
| Industry Standards  |   |  |  |  |  |  |
| UL Flammability Rating  | UL 94V-0                                |  |  |  |  |  |
| Packaging Features  |   |  |  |  |  |  |
| Packaging Type  | Box, Tube                               |  |  |  |  |  |
| Product Compliance<br>For compliance documentation, visit the product page on TE.com>   |   |  |  |  |  |  |
| EU RoHS Directive 2011/65/EU  | Compliant                               |  |  |  |  |  |
| EU ELV Directive 2000/53/EC   | Compliant                               |  |  |  |  |  |
| China RoHS 2 Directive MIIT Order No 32, 2016<br>EU REACH Regulation (EC) No. 1907/2006 | No Restricted Materials Above Threshold |  |  |  |  |  |

PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 3.5 mm [.137 in] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 1000 Series



Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC

Not Low Halogen - contains Br or Cl > 900 ppm.

Wave solder capable to 265°C

Halogen Content

Solder Process Capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# **Compatible Parts**




# Also in the Series | Dynamic 1000 Series



PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 3.5 mm [.137 in] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 1000 Series







# Customers Also Bought



| TE Part #5747845-4             | TE Part #1462039-2             | TE Part #3-1461491-3        | TE Part #350793-1             |
|--------------------------------|--------------------------------|-----------------------------|-------------------------------|
| 15 MSFL RCPT RA 318 (IN,FM,BL) | IM07CGR=IM RELAY 200mW 24V HDV | PCN-112D3MHZ,000            | 04P UMNL PIN HDR ASSY 94VO    |
| COP/TE                         |                                |                             |                               |
| TE Part #350787-1              | TE Part #825433-4              | TE Part #147721-3           | TE Part #1-1318114-3          |
| 02P UMNL PIN HDR ASSY 94VO     | MOD 2 PINHDR 1X4 P.            | 04 MODII HORZ SR SFMNT 30AU | DYNAMIC D-2100 TAB HSG 6P P/M |

# Documents

Product Drawings DYNAMIC 1500T HDR ASSY V 3P X BLACK GOLD

Japanese

### **CAD** Files

Customer View Model

ENG\_CVM\_CVM\_1-1827581-1\_C.2d\_dxf.zip

English

### 3D PDF

**C** For support call+1 800 522 6752

PCB Mount Header, Vertical, Wire-to-Board, 3 Position, 3.5 mm [.137 in] Centerline, Fully Shrouded, Gold, Through Hole - Solder, Dynamic 1000 Series



3D

Customer View Model ENG\_CVM\_CVM\_1-1827581-1\_C.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1-1827581-1\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages 1-1773732-4\_DYNAMIC\_SERIES\_CATALOG\_ENGLISH

Japanese

1-1773732-4\_DYNAMIC\_SERIES\_CATALOG\_ENGLISH

English

**Product Specifications** 

Application Specification

English

Agency Approvals TUV Certificate

English