1-1969603-0 ACTIVE

VAL-U-LOK

TE Internal #: 1-1969603-0

Rectangular Power Connectors, Housing, Receptacle, Wire-to-Board / Wire-to-Wire, 10 Position, 4.2 mm [.165 in] Centerline, Wire

& Cable, UL 94V-2

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Board, Wire-to-Wire

Number of Positions: 10

Centerline (Pitch): 4.2 mm [.165 in]

Features

Product Type Features

Rectangular Power Connector Type Connector & Housing Type Receptacle Connector System Wire-to-Board, Wire-to-Wire Sealable No Connector & Contact Terminates To Wire & Cable Configuration Features Number of Positions 10 Number of Rows 2 Electrical Characteristics Operating Voltage 600 VAC Contact Features Contact Retention Within Housing Without		
Connector System Sealable No Connector & Contact Terminates To Wire & Cable Configuration Features Number of Positions Number of Rows 2 Electrical Characteristics Operating Voltage 600 VAC Contact Features	Rectangular Power Connector Type	Housing
Sealable No Connector & Contact Terminates To Wire & Cable Configuration Features Number of Positions 10 Number of Rows 2 Electrical Characteristics Operating Voltage 600 VAC Contact Features	Connector & Housing Type	Receptacle
Connector & Contact Terminates To Configuration Features Number of Positions Number of Rows 2 Electrical Characteristics Operating Voltage 600 VAC Contact Features	Connector System	Wire-to-Board, Wire-to-Wire
Configuration Features Number of Positions 10 Number of Rows 2 Electrical Characteristics Operating Voltage 600 VAC Contact Features	Sealable	No
Number of Positions10Number of Rows2Electrical Characteristics600 VACContact Features600 VAC	Connector & Contact Terminates To	Wire & Cable
Number of Rows 2 Electrical Characteristics Operating Voltage 600 VAC Contact Features	Configuration Features	
Electrical Characteristics Operating Voltage 600 VAC Contact Features	Number of Positions	10
Operating Voltage 600 VAC Contact Features	Number of Rows	2
Contact Features	Electrical Characteristics	
	Operating Voltage	600 VAC
Contact Retention Within Housing Without	Contact Features	
	Contact Retention Within Housing	Without

Receptacle

Contact Type



Termination Features

Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	4.2 mm[.165 in]
Housing Color	White
Housing Material	Polyamide
Dimensions	
Connector Height	11.7 mm[.461 in]
Product Width	19.8 mm[.779 in]
Product Length	22.2 mm[.874 in]
Row-to-Row Spacing	4.2 mm[.165 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
CSA Rating	208567
UL Rating	Recognized
Agency/Standard	CSA, UL
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-2
Glow Wire Rating	GWT 750°C (Without Flame)
Packaging Features	
Packaging Quantity	500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant



China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Customers Also Bought





















Documents

Product Drawings
10P RCPT VAL-U-LOK GW

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-1969603-0_A_c-1-1969603-0-a.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-1969603-0_A_c-1-1969603-0-a.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-1969603-0_A_c-1-1969603-0-a.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

1-1773730-3 VAL-U-LOK Connectors with TPA Flyer

English

Product Specifications

Application Specification

English

Instruction Sheets

Instruction Sheet (U.S.)

Rectangular Power Connectors, Housing, Receptacle, Wire-to-Board / Wire-to-Wire, 10 Position, 4.2 mm [.165 in] Centerline, Wire & Cable, UL 94V-2



English

Agency Approvals

UL Report

English