# 1-1971905-7 ACTIVE

#### **GRACE INERTIA 3.3**

TE Internal #: 1-1971905-7

Rectangular Power Connectors, Housing, Plug, Wire-to-Board, 14 Position, 3.3 mm [.129 in] Centerline, Wire & Cable, UL 94V-0,

**GRACE INERTIA 3.3** 

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors > Glow Wire GRACE INERTIA Plug











Rectangular Power Connector Type: Housing

Connector & Housing Type: Plug
Connector System: Wire-to-Board

Number of Positions: 14

Centerline (Pitch): 3.3 mm [ .129 in ]

All Glow Wire GRACE INERTIA Plug (78)

#### **Features**

#### **Product Type Features**

| Rectangular Power Connector Type  | Housing       |  |
|-----------------------------------|---------------|--|
| Connector & Housing Type          | Plug          |  |
| Connector System                  | Wire-to-Board |  |
| Sealable                          | No            |  |
| Connector & Contact Terminates To | Wire & Cable  |  |
| Configuration Footunes            |               |  |

#### **Configuration Features**

| Number of Positions        | 14 |
|----------------------------|----|
| Number of Power Positions  | 14 |
| Number of Signal Positions | 14 |
| Number of Rows             | 2  |

#### **Electrical Characteristics**

| Operating | g Voltage | 250 VDC |
|-----------|-----------|---------|
|           |           |         |



### **Body Features**

| body i catalog                                 |                            |
|--|----------------------------|
| Connector & Keying Code                        | A                          |
| Contact Features                               |                            |
| Contact Mating Area Plating Material           | Tin                        |
| Contact Current Rating (Max)                   | 4 A                        |
| Contact Retention Within Housing               | With                       |
| Contact Type                                   | Receptacle                 |
| Contact Mating Area Plating Material Thickness | 2 μm[78.73 μin]            |
| Termination Features                           |                            |
| Termination Method to Wire & Cable             | Crimp                      |
| Mechanical Attachment                          |                            |
| Mating Alignment Type                          | Keyed                      |
| Mating Retention                               | With                       |
| Mating Alignment                               | With                       |
| Mating Retention Type                          | Latch                      |
| Connector Mounting Type                        | Cable Mount (Free-Hanging) |
| Housing Features                               |                            |
| Centerline (Pitch)                             | 3.3 mm[.129 in]            |
| Housing Color                                  | Natural                    |
| Housing Material                               | PA 66 GF                   |
| Dimensions                                     |                            |
| Wire Size                                      | 414.44 – 1045.97 CMA       |
| Row-to-Row Spacing                             | 5.2 mm[.205 in]            |
| Usage Conditions                               |                            |
| Operating Temperature Range                    | -30 - 105 °C[-22 - 221 °F] |
| Operation/Application                          |                            |
| Circuit Application                            | Power & Signal             |
| Industry Standards                             |                            |
| UL Flammability Rating                         | UL 94V-0                   |
| Glow Wire Rating                               | GWT 750°C (Without Flame)  |
| Packaging Features                             |                            |
|  |                            |



| Packaging Quantity | 800 |
|--------------------|-----|
| Packaging Method   | Bag |

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU                  | Compliant   |
|---|---|
| EU ELV Directive 2000/53/EC                   | Compliant   |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold   |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content                               | Not Low Halogen - contains Br or Cl > 900 ppm.  |
| Solder Process Capability                     | Not reviewed for solder process capability  |

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## **Compatible Parts**



Also in the Series | GRACE INERTIA 3.3





PCB Latches, Locks & Retainers(7)



Power Contacts(3)



Rectangular Connector Locking(8)



## Customers Also Bought
















### **Documents**

#### **Product Drawings**

PLUG HOUSING 14POS, KEYING-A, NEW GIC3.3

English

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-1971905-7\_C.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1971905-7\_C.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1971905-7\_C.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Rectangular Power Connectors, Housing, Plug, Wire-to-Board, 14 Position, 3.3 mm [. 129 in] Centerline, Wire & Cable, UL 94V-0, GRACE INERTIA 3.3



Datasheets & Catalog Pages

GI3.3\_QRG\_CN

**Product Specifications** 

**Application Specification** 

English

Product Environmental Compliance

TE Material Declaration

English