

SMA-A0204BTN820R

✓ ACTIVE

Neohm | Neohm SMA-A

TE Internal #: 1-2176315-2

820 Ω, Thin Film, Precision Resistor, .1 %, 2 Termination, 0204,  
Taped & Reeled, .4 W, ±15 ppm/°C, Metal Electrode Leadless Face  
(MELF), Neohm SMA-A

[View on TE.com >](#)



Passive Components > Resistors > Surface Mount Resistors



Resistor Type: **Precision Resistor**  
Number of Terminations: **2**  
Package Size Code: **0204**  
Packaging Method: **Taped & Reeled**  
Passive Component Tolerance: **.1 %**

Features

Product Type Features

|                   |                    |
|-------------------|--------------------|
| Product Type      | Fixed Resistor     |
| Resistor Type     | Precision Resistor |
| Package Size Code | 0204               |
| Element Type      | Thin Film          |

Configuration Features

|                     |   |
|---------------------|---|
| Number of Resistors | 1 |
|---------------------|---|

Electrical Characteristics

|                             |           |
|-----------------------------|-----------|
| Voltage Rating              | 200 V     |
| Passive Component Tolerance | .1 %      |
| Resistance Class            | Up to 1kΩ |
| Resistance Value            | 820 Ω     |
| Power Rating                | .4 W      |

Termination Features

|                        |   |
|------------------------|---|
| Number of Terminations | 2 |
|------------------------|---|



|                                         |                                      |
|-----------------------------------------|--------------------------------------|
| Surface Mount Resistor Termination Type | Metal Electrode Leadless Face (MELF) |
|-----------------------------------------|--------------------------------------|

Dimensions

|                              |              |
|------------------------------|--------------|
| Passive Component Dimensions | 3.5 x 1.4 mm |
|------------------------------|--------------|

Usage Conditions

|                             |              |
|-----------------------------|--------------|
| Operating Temperature Range | -55 – 155 °C |
| Temperature Coefficient     | ±15 ppm/°C   |

Packaging Features

|                  |                |
|------------------|----------------|
| Packaging Method | Taped & Reeled |
|------------------|----------------|

Product Compliance

For compliance documentation, visit the product page on TE.com>

|                                               |                                                                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| EU RoHS Directive 2011/65/EU                  | Compliant                                                                                                                       |
| EU ELV Directive 2000/53/EC                   | Compliant                                                                                                                       |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold                                                                                         |
| EU REACH Regulation (EC) No. 1907/2006        | Current ECHA Candidate List: JUNE 2023 (235)<br>Candidate List Declared Against: JUNE 2023 (235)<br>Does not contain REACH SVHC |
| Halogen Content                               | BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.                                                                          |
| Solder Process Capability                     | Reflow solder capable to 260°C                                                                                                  |

Product Compliance Disclaimer


This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts


SMA-A0204BTNX820R

820 Ω, Thin Film, Precision Resistor, .1 %, 2 Termination, 0204, Taped & Reeled, .4 W, ±15 ppm/°C, Metal Electrode Leadless Face (MELF), Neohm SMA-A







TE Part # 6-2176314-9  
MELF SMA-A 10R 1% 50PPM 0102 0.3 W




TE Part # 3-2176315-2  
MELF SMA\_A 39K 0.1% 15PPM 0204 0.4W



TE Part # 2176316-5  
MELF SMA\_A 220R 0.1% 15PPM 0207 1W



TE Part # 9-2176315-8  
MELF SMA-A 1M0 1% 50PPM 0204 0.4 W




TE Part # 9-2176316-4  
MELF SMA-A 330K 1% 50PPM 0207 1W

Also in the Series | Neohm SMA-A




Surface Mount Resistors(384)


Customers Also Bought



TE Part #292132-3  
CT 2mm Post Header Asmbly: Box V DIP



TE Part #7-534206-0  
40 MODII VRT DR CE 100/115




TE Part #825440-3  
MOD 2 PINHDR 2X03P.




TE Part #2-826632-0  
20P AMPMODU II PIN HDR.



TE Part #2154829-3  
High Power Inverted Thru Board Con 4 Pos



TE Part #1-2176315-5  
MELF SMA\_A 1K5 0.1% 15PPM 0204 0.4W



TE Part #2176315-8  
MELF SMA\_A 390R 0.1% 15PPM 0204 0.4W



Documents

Product Drawings

MELF SMA\_A 820R 0.1% 15PPM 0204 0.4W

English

CAD Files

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1-2176315-2\_BA.2d\_dxf.zip

English

Customer View Model

ENG\_CVM\_CVM\_1-2176315-2\_BA.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1-2176315-2\_BA.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

SMA-A-1017

English