RLW73PH2FR12TE <

CGS | CGS RLW73

TE Internal #: 1-2176545-4 .12 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1020, Taped & Reeled, 2 W, ±200 ppm/°C, Solder, 2.5 x 5 x .6 mm, CGS RLW73

View on TE.com >

Passive Components > Resistors > Surface Mount Resistors



Resistor Type: Current Sensing Resistor

Number of Terminations: 2

Package Size Code: 1020

Packaging Method: Taped & Reeled

Passive Component Tolerance: 1%

Features



Product Type Features

Product Type	Fixed Resistor
Resistor Type	Current Sensing Resistor
Package Size Code	1020
Element Type	Thick Film
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Passive Component Tolerance	1 %
Resistance Class	Up to 1kΩ
Resistance Value	.12 Ω
Power Rating	2 W
Termination Features	
Number of Terminations	2
Surface Mount Resistor Termination Type	Solder

RLW73PH2FR12TE

.12 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1020, Taped & Reeled, 2 W, ±200 ppm/°C, Solder, 2.5 x 5 x .6 mm, CGS RLW73



Dimensions

Passive Component Dimensions	2.5 x 5 x .6 mm
Usage Conditions	
Operating Temperature Range	-55 – 155 °C
Temperature Coefficient	±200 ppm/°C
Packaging Features	
Packaging Method	Taped & Reeled

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC

Halogen Content

Solder Process Capability

BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.

Reflow solder capable to 260°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts


RLW73PH2FR12TE

.12 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1020, Taped & Reeled, 2 W, ±200 ppm/°C, Solder, 2.5 x 5 x .6 mm, CGS RLW73





Also in the Series | CGS RLW73



Documents

Product Drawings RLW73P H2 1% R12 200ppm 4k RL

English

CAD Files

Customer View Model

ENG_CVM_CVM_1-2176545-4_BA.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2176545-4_BA.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1-2176545-4_BA.2d_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages CGS Wide Terminal Current Sense Resistor RLW73 English Wide Terminal Current Sense Resistor - Type RLW73 Series English