# RLC73K2ER825FTD <

# CGS | CGS RLC73

TE Internal #: 1-2176586-4 .825 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1210, Taped & Reeled, .5 W, ±200 ppm/°C, Solder, 3.1 x 2.6 x .55 mm, CGS RLC73

## View on TE.com >

#### Passive Components > Resistors > Surface Mount Resistors



### Resistor Type: Current Sensing Resistor

Number of Terminations: 2

Package Size Code: 1210

Packaging Method: Taped & Reeled

Passive Component Tolerance: 1%

# Features

connectivity

# Product Type Features

Product Type	Fixed Resistor
Resistor Type	Current Sensing Resistor
Package Size Code	1210
Element Type	Thick Film
Configuration Features	
Number of Resistors	1
Electrical Characteristics	
Passive Component Tolerance	1 %
Resistance Class	Up to 1kΩ
Resistance Value	.825 Ω
Power Rating	.5 W
Termination Features	
Number of Terminations	2
Surface Mount Resistor Termination Type	Solder

## RLC73K2ER825FTD

.825 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1210, Taped & Reeled, .5 W, ±200 ppm/°C, Solder, 3.1 x 2.6 x .55 mm, CGS RLC73



#### Dimensions

Passive Component Dimensions	3.1 x 2.6 x .55 mm
Usage Conditions	
Operating Temperature Range	-55 – 155 °C
Temperature Coefficient	±200 ppm/°C
Packaging Features	
Packaging Method	Taped & Reeled

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC

Halogen Content

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

#### Solder Process Capability

## Reflow solder capable to 260°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked.Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

# **Compatible Parts**

## RLC73K2ER825FTD

.825 Ω, Thick Film, Current Sensing Resistor, 1 %, 2 Termination, 1210, Taped & Reeled, .5 W, ±200 ppm/°C, Solder, 3.1 x 2.6 x .55 mm, CGS RLC73





# Also in the Series | CGS RLC73



# Documents

Product Drawings RLC73K 2E R825 1% 5K RL

English

## **CAD** Files

**Customer View Model** 

ENG\_CVM\_CVM\_1-2176586-4\_BA.3d\_igs.zip

English

Customer View Model

ENG\_CVM\_CVM\_1-2176586-4\_BA.3d\_stp.zip

English

Customer View Model

ENG\_CVM\_CVM\_1-2176586-4\_BA.2d\_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages SMD Low Ohmic - Current Sense Resistors - Type RLC73 Series

English