
1-2199299-2 <

DIPLOMATE TE Internal #: 1-2199299-2 DIP Sockets, Stamped & Formed, 28 Position, Standard Profile, Straight, Tin, -40 – 105 °C [-40 – 221 °F] View on TE.com >



Connectors > Socket Connectors > IC Sockets > DIP Sockets > DIP Socket: Standard, Stamped & Formed, Open, Tin



Contact Fabrication: Stamped & Formed

Number of Positions: 28

Connector Profile: Standard

Row-to-Row Spacing: 15.24 mm [.6 in]

Leg Style: Straight

All DIP Socket: Standard, Stamped & Formed, Open, Tin (3)

Features

Product Type Features

Leg Style

Connector & Contact Terminates To

Straight

Printed Circuit Board

Configuration Features

Number of Rows	2
PCB Mount Orientation	Vertical
Number of Positions	28
Electrical Characteristics	
Insulation Resistance	1000 MΩ
Contact Resistance	20 mΩ
Body Features	
Sleeve Material	Brass/Copper
Sleeve Plating Material	Tin/Lead
Frame Style	Ladder
Connector Profile	Standard
Contact Features	
Mating Contact Type	Dual Leaf

1-2199299-2

DIP Sockets, Stamped & Formed, 28 Position, Standard Profile, Straight, Tin, -40 – 105 °C [-40 – 221 °F]



IC Socket Type	DIP
Contact Type	Pin
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Fabrication	Stamped & Formed
Contact Mating Area Plating Material	Tin
	60 µin
Contact Current Rating (Max)	1 A
Termination Features	
Termination Post & Tail Length	3 mm[.118 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Polarization
Mating Alignment	With
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	PBT GF30
Housing Color	Black
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Profile Height from PCB	5.1 mm[.2 in]
Row-to-Row Spacing	15.24 mm[.6 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Box & Tube, Tube

C For support call+1 800 522 6752

1-2199299-2

DIP Sockets, Stamped & Formed, 28 Position, Standard Profile, Straight, Tin, -40 – 105 °C [-40 – 221 °F]



For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-



Customers Also Bought





1-2199299-2

DIP Sockets, Stamped & Formed, 28 Position, Standard Profile, Straight, Tin, -40 – 105 °C [-40 – 221 °F]



Documents

Product Drawings 28P,DIP SKT,600 CL,LDR,PB FREE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2199299-2_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2199299-2_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2199299-2_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages DIP Sockets Quick Reference Guide (EN)

English