TE Internal #: 1-2293551-1

Housing for Female Terminals, Wire-to-Panel / Wire-to-Wire, 62

Position, .197 in / .157 in [5 mm / 4 mm] Centerline, Sealable, Black,

Wire & Cable

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings











Connector System: Wire-to-Panel, Wire-to-Wire

Number of Positions: 62

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 4 mm, 5 mm [.157 in, .197 in]

Sealable: Yes

Features

Product Type Features

Mixed & Hybrid Connector	Yes
Connector Shape	Rectangular
Connector System	Wire-to-Panel, Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	Yes
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Locking Lance
Configuration Features	
Number of Positions	62
Number of Rows	3, 4
Electrical Characteristics	
Operating Voltage	36 VDC
Nominal Voltage Architecture	12 V



Primary Product Color	Black
Connector & Keying Code	A
Contact Features	
Contact Size	1.5K, 2.8mm
Contact Type	Receptacle
Mating Tab Width	2.8 mm[.11 in]
Contact Current Rating (Max)	40 A
Mechanical Attachment	
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Centerline (Pitch)	4 mm, 5 mm[.157 in][.197 in]
Dimensions	
Row-to-Row Spacing	4 mm, 5.5 mm[.157 in][.216 in]
Usage Conditions	
Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]
Operation/Application	
Circuit Application	Power & Signal
Other	
Connector Position Assurance Capable	Yes

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
() () ()	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC



Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per
	homogenous material. Also BFR/CFR/PVC
	Free

Solder Process Capability

Not reviewed for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # CAT-L489-H342



TE Part # 1-1718324-1 1.5/2.8MM TAB HSG.,62POS.,ASSY



TE Part # 828905-1
SINGLE-WIRE-SEAL(5MM HOLE)





Customers Also Bought













TE Part #CB0934-000 FL2500-NO.4-J2-0-55MM



Documents

Product Drawings

62POS,MIXED,REC HSG,ASSY,SLD

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2293551-1_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2293551-1_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2293551-1_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

German