1-2323832-1 ACTIVE

Power Double Lock

TE Internal #: 1-2323832-1

Power Contacts, Contact, 300 VAC, Tin, 18 – 16 AWG Wire Size, Wire & Cable, Crimp, Power, Socket, -30 – 150 °C [-22 – 221 °F],

Power Double Lock

View on TE.com >



Connectors > Power Connectors > Power Contacts











Power Contact Type: Contact
Operating Voltage: 300 VAC

Contact Mating Area Plating Material: Tin

Wire Size: 18 – 16 AWG

Sealable: No

Features

Product Type Features

| Compatible With Discrete Wire Type | Stranded |
|------------------------------------|--------------|
| Power Contact Type | Contact |
| Sealable | No |
| Connector & Contact Terminates To | Wire & Cable |
| Electrical Characteristics | |
| Operating Voltage | 300 VAC |

Contact Features

| Contact Mating Area Plating Material | Tin |
|---|------------------|
| Contact Current Rating (Max) | 8 A |
| Contact Type | Socket |
| Contact Retention Within Housing | With |
| Contact Base Material | Copper Alloy |
| Wire Contact Termination Area Plating Thickness | .8 μm[31.49 μin] |
| Wire Contact Termination Area Plating Material | Pre-Tin |



| Contact Orientation | Straight |
|--------------------------------------|-------------------------------|
| Termination Features | |
| Termination Method to Wire & Cable | Crimp |
| Mechanical Attachment | |
| Wire Insulation Support | With |
| Dimensions | |
| Wire Size | 18 – 16 AWG |
| Compatible Insulation Diameter Range | 1.75 – 2.5 mm[.069 – .098 in] |
| Usage Conditions | |
| Operating Temperature Range | -30 – 150 °C[-22 – 221 °F] |
| Operation/Application | |
| Circuit Application | Power |
| Packaging Features | |
| Packaging Quantity | 4000 |
| Packaging Method | Reel |

Product Compliance

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products

Power Contacts, Contact, 300 VAC, Tin, 18 – 16 AWG Wire Size, Wire & Cable, Crimp, Power, Socket, -30 – 150 °C [-22 – 221 °F], Power Double Lock



will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | Power Double Lock








Insertion & Extraction Tools(2)



Power Contacts(23)



Rectangular Connector Locking(14)



Documents

Product Drawings

PDL REC TERMINAL 18-20 AWG w/lube

English

CAD Files

3D PDF

3D

Customer View Model



ENG_CVM_CVM_1-2323832-1_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2323832-1_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-2323832-1_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English