TE Internal #: 1-2355091-4

Connector Assembly, Plug, Wire-to-Board, 14 Position, .047 in [1.2 mm] Centerline, 1 Row, Natural, Mating Retention, Printed Circuit

Board

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings











Connector Product Type: Connector Assembly

Connector & Housing Type: Plug
Connector System: Wire-to-Board

Number of Positions: 14

Centerline (Pitch): 1.2 mm [.047 in]

### **Features**

### Product Type Features

Connector Product Type	Connector Assembly
Connector & Housing Type	Plug
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	14
Number of Rows	1
Electrical Characteristics	
Termination Resistance	20 mΩ
Dielectric Withstanding Voltage (Max)	250 VAC
Insulation Resistance	100 MΩ
Operating Voltage	50 VAC

Natural

**Body Features** 

Primary Product Color



#### **Contact Features**

Contact Features	
Contact Retention Within Housing	With
Contact Layout	Inline
Contact Type	Pin
PCB Contact Termination Area Plating Material Finish	Matte
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Pre-Tin
Contact Base Material	Brass
Contact Current Rating (Max)	2 A
Mechanical Attachment	
Locking Latch Between Cavity Number	None
PCB Mount Alignment Type	None
Strain Relief	With
Contact Retention Type Within Housing	Press-Fit
PCB Mount Alignment	Without
PCB Mount Retention	Without
PCB Mount Retention Type	Solder
Mating Retention Type	Detent Latching
Mating Retention	With
Connector Mounting Type	Board Mount
Housing Features	
Housing Entry Configuration	Both Ends Open
Housing Material	PA 6T
Centerline (Pitch)	1.2 mm[.047 in]
Dimensions	
Connector Length	19.9 mm[.783 in]
Connector Height	6.7 mm[.263 in]
Connector Width	6.85 mm[.269 in]
PCB Thickness (Recommended)	1.6 mm[.062 in]
Usage Conditions	
Operating Temperature Range	30 – 85 °C

Operation/Application



Circuit Application	Power & Signal
Industry Standards	
RAST Version	None
Agency/Standard	UL
Approved Standards	UL E28476
UL Flammability Rating	UL 94V-0
Packaging Features	
Packaging Method	Reel/Carton

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts





# Customers Also Bought



TE Part #1-2355091-0 MICRO CT CONN SINGLE ROW HDR ASSY(V)10p



TE Part #1-2355091-9 MICRO CT CONN SINGLE ROW HDR ASSY(V)19p



TE Part #2-2355091-1 MICRO CT CONN SINGLE ROW HDR ASSY(V)21p



TE Part #2-2355091-4 MICRO CT CONN SINGLE ROW HDR ASSY(V)24p



TE Part #2-2355091-5 MICRO CT CONN SINGLE ROW HDR ASSY(V)25p



TE Part #2355091-5 MICRO CT CONN SINGLE ROW HDR ASSY(V) 5p



TE Part #2355091-6 MICRO CT CONN SINGLE ROW HDR ASSY(V) 6p



TE Part #2355091-7 MICRO CT CONN SINGLE ROW HDR ASSY(V) 7p



# **Documents**

## **Product Drawings**

MICRO CT CONN SINGLE ROW HDR ASSY(V)14p

English

### **CAD Files**

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_1-2355091-4\_E.2d\_dxf.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_1-2355091-4\_E.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-2355091-4\_E.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

# Datasheets & Catalog Pages

1.2mm AMP Micro CT Connector Series

English

**Product Specifications** 

**Product Specification** 

Japanese

Product Environmental Compliance

**Product Compliance** 

English

**Product Compliance** 

English

**Agency Approvals** 

UL

English