TE Internal #: 1-2379397-1

Internal I/O Connectors, Mini Cool Edge I/O (MCIO), Cable Plug Assembly, Vertical, Cable-to-Board, SFF-TA-1016, 74 Position,

Surface Mount

View on TE.com >



Connectors > PCB Connectors > Internal I/O Connectors











Internal I/O Connector Type: Mini Cool Edge I/O (MCIO)

Connector Mates With: Cable Plug Assembly

PCB Mount Orientation: Vertical
Connector System: Cable-to-Board
Industry Standard: SFF-TA-1016

Features

Product Type Features

| Internal I/O Connector Type | Mini Cool Edge I/O (MCIO) |
|-----------------------------------|---------------------------|
| Connector Mates With | Cable Plug Assembly |
| Connector System | Cable-to-Board |
| Connector & Contact Terminates To | Printed Circuit Board |

Configuration Features

| Number of Rows | 2 |
|-----------------------|----------|
| PCB Mount Orientation | Vertical |
| Number of Positions | 74 |

Contact Features

| Contact Mating Area Plating Material | Gold |
|---|--------------|
| Contact Underplating Material | Nickel |
| PCB Contact Termination Area Plating Material | Tin |
| Contact Base Material | Copper Alloy |
| Contact Current Rating (Max) | 1.1 A |



| Contact Mating Area Plating Material Thickness | .381 µm[15 µin] |
|--|-----------------|
| | |

| Termination Features | |
|---|---------------------------|
| Termination Method to Printed Circuit Board | Surface Mount |
| Mechanical Attachment | |
| Connector Mounting Type | Board Mount |
| Housing Features | |
| Centerline (Pitch) | .6 mm[.023 in] |
| Usage Conditions | |
| Operating Temperature Range | -55 – 85 °C[-67 – 185 °F] |
| Operation/Application | |
| Circuit Application | Signal |

SFF-TA-1016

Product Compliance

Industry Standard

Industry Standards

For compliance documentation, visit the product page on TE.com>

| EU RoHS Directive 2011/65/EU | Compliant |
|---|---|
| EU ELV Directive 2000/53/EC | Compliant |
| China RoHS 2 Directive MIIT Order No 32, 2016 | No Restricted Materials Above Threshold |
| EU REACH Regulation (EC) No. 1907/2006 | Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC |
| Halogen Content | Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free |
| Solder Process Capability | Not reviewed for solder process capability |

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts









Customers Also Bought















Documents

Product Drawings

MCIO INTERGRATED CONN, V/T,8X, SMT TYPE

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-2379397-1_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-2379397-1_1.3d_igs.zip



English

Customer View Model

ENG_CVM_CVM_1-2379397-1_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English