

TE Internal #: 1-2435262-0

Snap Action Switches, Single Pole - Double Throw Configuration (Pole-Throw), Roller, Simulated Actuator Style, 26 A, 125 VAC, 250

VDC

View on TE.com >




Relays, Contactors & Switches > Switches > Snap Action Switches











Configuration (Pole-Throw): Single Pole - Double Throw

Actuator Style: Roller, Simulated

Snap Action Switch Contact Current Rating: **26 A**Snap Action Switch Voltage Rating: **250 VDC** 

## **Features**

### **Product Type Features**

Switch Type  Actuator Style  Roller, Simulated  Switch Connection Type  Quick Connect Terminal  Switch Style  Miniature	Product Type	Switch
Switch Connection Type Quick Connect Terminal	Switch Type	Snap Action
71	Actuator Style	Roller, Simulated
Switch Style Miniature	Switch Connection Type	Quick Connect Terminal
	Switch Style	Miniature

## **Configuration Features**

Operating Position	18.7 mm[.736 in]
Configuration (Pole-Throw)	Single Pole - Double Throw

#### **Electrical Characteristics**

Snap Action Switch Voltage Rating	250 VDC
-----------------------------------	---------

## **Body Features**

Movement Differential	1.1 mm[.043 in]
Releasing Force	25 g[.881 oz]

#### **Contact Features**



#### **Termination Features**

Termination Type	.25 x .2 Quick Connect Terminals
Mechanical Attachment	
Snap Action Switch Mounting Angle	Vertical
Housing Features	
Housing Material	PBT
Dimensions	
Pre Travel	5.5 mm[.216 in]
Operation/Application	
Operating Force	205 g[7.23 oz]
Other	
Over Travel	1.9 mm[.074 in]

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not reviewed for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulations, TE's information on SVHC in articles for this part number is still based on the European Chemical Agency (ECHA) 'Guidance on requirements for substances in articles' (Version: 2, April 2011), applying the 0.1% weight on weight concentration threshold at the finished product level. TE is aware of the European Court of Justice ruling of September 10th, 2015 also known as O5A (Once An

Snap Action Switches, Single Pole - Double Throw Configuration (Pole-Throw), Roller, Simulated Actuator Style, 26 A, 125 VAC, 250 VDC



Article Always An Article) stating that, in case of 'complex object', the threshold for a SVHC must be applied to both the product as a whole and simultaneously to each of the articles forming part of its composition. TE has evaluated this ruling based on the new ECHA "Guidance on requirements for substances in articles" (June 2017, version 4.0) and will be updating its statements accordingly.

# Compatible Parts



## **Documents**

### **Product Drawings**

HCP26A, Hvt Force, 0.250 Term. Smt Roller

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_1-2435262-0\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-2435262-0\_A.3d\_stp.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-2435262-0\_A.2d\_dxf.zip

English

3D PDF

3D

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

## Datasheets & Catalog Pages

ALCOSWITCH\_HCP\_SERIES

English