


Buchanan

TE Internal #: 1-282843-1 PCB Terminal Blocks, Header, Wire-to-Board, 11 Position, .4 in [10.16 mm] Centerline, 1 Row, 90° Wire Entry Angle, 30 – 12 AWG Wire Size

View on TE.com >

Connectors > Terminal Blocks & Strips > PCB Terminal Blocks



Terminal Block Connector Type: Header

Connector System: Wire-to-Board

Number of Positions: 11

Centerline (Pitch): 10.16 mm [.4 in]

Number of Rows: 1

Features



Product Type Features

Wire Protection	With
Terminal Block Connector Type	Header
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Stacked Levels	Without
Wire Entry Location	Side
Stacking Configuration	Side Stackable
Number of Positions	11
Number of Rows	1
Wire Entry Angle	90°
Electrical Characteristics	
Operating Voltage	600 VAC

C For support call+1 800 522 6752

PCB Terminal Blocks, Header, Wire-to-Board, 11 Position, .4 in [10.16 mm] Centerline, 1 Row, 90° Wire Entry Angle, 30 – 12 AWG Wire Size



Primary Product Color	Green
Product Orientation	Vertical
Contact Features	
Contact Mating Area Plating Material	Tin
Contact Base Material	Brass
Contact Current Rating (Max)	17.5 A
Termination Features	
Termination Post & Tail Length	3.5 mm[.138 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Screw Plating Material	Nickel
Screw Material	Brass
Thread Size	M3
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	PA 66
Centerline (Pitch)	10.16 mm[.4 in]

Dimensions

Wire Size	.05 – 3 mm²
Usage Conditions	
Operating Temperature Range	-40 – 110 °C[-40 – 230 °F]
Operation/Application	
Circuit Application	Power & Signal
Identification Marking	
Marking Color	Black
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Compliant with Exemptions
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold

PCB Terminal Blocks, Header, Wire-to-Board, 11 Position, .4 in [10.16 mm] Centerline, 1 Row, 90° Wire Entry Angle, 30 – 12 AWG Wire Size



EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (.8% in Component Part) Article Safe Usage Statements Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach

Compatible Parts



Customers Also Bought



PCB Terminal Blocks, Header, Wire-to-Board, 11 Position, .4 in [10.16 mm] Centerline, 1 Row, 90° Wire Entry Angle, 30 – 12 AWG Wire Size







Documents

Product Drawings TERMI-BLOK PCB MOUNT 90 11P.

English

CAD Files **Customer View Model** ENG_CVM_CVM_1-282843-1_E1.3d_stp.zip

English

Customer View Model

ENG_CVM_CVM_1-282843-1_E1.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-282843-1_E1.3d_igs.zip

English

Customer View Model

ENG_CVM_1-282843-1_E.3d_igs.zip

English

Customer View Model

ENG_CVM_1-282843-1_E.3d_stp.zip

English

Customer View Model

ENG_CVM_1-282843-1_E.2d_dxf.zip

English

3D PDF

English

C For support call+1 800 522 6752

PCB Terminal Blocks, Header, Wire-to-Board, 11 Position, .4 in [10.16 mm] Centerline, 1 Row, 90° Wire Entry Angle, 30 – 12 AWG Wire Size



By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages BUCHANAN TERMINAL BLOCKS CATALOG - EUROSTYLE TERMINAL BLOCKS

English

1-1773458-1_EURO_STYLE_TERMINAL_BLOCKS_QRG

English

Product Specifications

Application Specification

English

Agency Approvals

UL

English