# 1-292161-3 ACTIVE

#### **AMP CT**

TE Internal #: 1-292161-3

PCB Mount Header, Vertical, Wire-to-Board, 13 Position, 2 mm [. 079 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder,

AMP CT


View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles > CT 2mm Post Header Assembly with Kink - Vertical











Connector System: Wire-to-Board

Number of Positions: 13

Number of Rows: 1

Centerline (Pitch): 2 mm [.079 in ]
PCB Mount Orientation: Vertical

All CT 2mm Post Header Assembly with Kink - Vertical (47)

### **Features**

### **Product Type Features**

Connector System	Wire-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header
Configuration Features	
Number of Positions	13
Number of Rows	1
PCB Mount Orientation	Vertical
Electrical Characteristics	
Operating Voltage	125 VAC



CB Contact Termination Area Plating Material Thickness 1 -	5 mm[.177 in]
CB Contact Termination Area Plating Material Thickness 1 -	
	2 um[20 27 70 72 uin]
	– 2 µm[39.37 – 78.73 µin]
ontact Layout Inl	line
ating Pin Diameter .6	mm[.024 in]
ontact Mating Area Plating Material Thickness 1 -	– 2 µm[39.37 – 78.73 µin]
ontact Shape & Form Ro	ound
ontact Mating Area Plating Material Finish Ma	latte
CB Contact Termination Area Plating Material Tir	in
ontact Base Material Br	rass
ontact Mating Area Plating Material Tir	n
ontact Type Pir	in
ontact Current Rating (Max) 4 A	A
mination Features	
ound Termination Post & Tail Diameter .6	mm[.024 in]
rmination Post & Tail Length 3.2	2 mm[.126 in]
rmination Method to Printed Circuit Board Th	hrough Hole - Solder
chanical Attachment	
ating Alignment Type Po	olarization
ating Retention W	/ithout
nel Mount Feature W	/ith
CB Mount Retention Type Kir	inked Legs
onnector Mounting Type Bo	oard Mount
ating Alignment W	/ith
CB Mount Alignment W	/ithout
CB Mount Retention W	/ith
ising Features	
ousing Material Ny	ylon 66
enterline (Pitch) 2 r	mm[.079 in]
ensions	
onnector Length 27	7.8 mm[1.095 in]



Connector Height	6.8 mm[.267 in]
Connector Width	3.6 mm[.141 in]
PCB Thickness (Recommended)	.8 mm[.031 – .063 in]
Usage Conditions	
Operating Temperature Range	-40 - 221 °C[-40 - 105 °F]
Operation/Application	
Assembly Process Feature	Pick and Place Cover
Circuit Application	Power & Signal
Circuit Application  Industry Standards	Power & Signal
	Power & Signal  CSA, UL
Industry Standards	
Industry Standards  Agency/Standard	CSA, UL
Industry Standards  Agency/Standard  Approved Standards	CSA, UL CSA LR7189, UL E28476

### **Product Compliance**

Packaging Type

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 240°C

Bag, Box

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part

PCB Mount Header, Vertical, Wire-to-Board, 13 Position, 2 mm [.079 in] Centerline, Partially Shrouded, Tin, Through Hole - Solder, AMP CT



numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts



Common Termination Contacts —

POWER TRIPLE LOCK



# Also in the Series | AMP CT



PCB Connector Mounting(46)



PCB Headers & Receptacles(756)



Wire-to-Board Connector Assemblies & Housings(256)



Wire-to-Board Connector Contacts(8)


# **Customers Also Bought**



TE Part #292161-6 CT 2mm Post Header Asmbly: Box V DIP



TE Part #292253-2 CT CONN MT HDR ASSY H 2P NAT



TE Part #2-292161-3 CT P/HDR ASSY V 3P W/KINK BLUE



TE Part #292207-3 MINI CT SGL DIP V 3P NAT



TE Part #292254-3 CT RELAY HDR ASSY 3P NAT



TE Part #292254-2 CT RELAY HDR ASSY 2P NAT TE Part #8-292155-3 SGL HDR PANEL MOUNT ASSY



#### **Documents**

### **Product Drawings**

CT P/HDR ASSY V 13P W/KINK NAT

English

#### **CAD Files**

**Customer View Model** 

ENG\_CVM\_CVM\_1-292161-3\_A.2d\_dxf.zip

English

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-292161-3\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-292161-3\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

### **Product Specifications**

**Product Specification** 

English

**Product Specification** 

English

AMP COMMON TERMINATION (CT), CONNECTOR, 2mm PITCH, M/T TYPE, LEAD FREE VERSION

Japanese

**Product Specification** 

Japanese

**Product Environmental Compliance** 

MD\_1-292161-3\_030320181232\_dmtec

English

MD\_1-292161-3\_030320181232\_dmtec

English