

STRATO-THERM DIAMOND GRIP

TE Internal #: 1-321897-5 Closed Ring Tongue Terminal, 22 – 16 AWG, #8 / M5 Stud Size, 5.2 mm [.205 in] Stud Diameter, Closed Barrel, Straight, STRATO-THERM DIAMOND GRIP

View on TE.com >

Terminals & Splices > Ring Terminals



Ring Terminal Product Type: Closed Ring Tongue Terminal

Wire Size: 509 – 3260 CMA

Stud Size: #8, M5

Features

Product Type Features

Ring Terminal Product Type	Closed Ring Tongue Terminal
Stud Size	#8, M5
Sealable	No
Wire Insulation Support Retention Type	Insulation Support
Configuration Features	
Number of Holes	1
Contact Features	
Barrel Type	Closed
Terminal Orientation	Straight
Terminal Plating Material	Unplated
Mechanical Attachment	
Wire Insulation Support	With
Dimensions	
Wire Size	509 – 3260 CMA
Stud Diameter	5.2 mm[.205 in]



1-321897-5

Closed Ring Tongue Terminal, 22 – 16 AWG, #8 / M5 Stud Size, 5.2 mm [.205 in] Stud Diameter, Closed Barrel, Straight, STRATO-THERM DIAMOND GRIP



Tongue Thickness	.79 mm[.031 in]
Product Length	20.22 mm[.796 in]
Compatible Insulation Diameter (Max)	3.56 mm[.14 in]
Compatible Insulation Diameter Range	2.67 – 3.56 mm[.105 – .14 in]
Usage Conditions	
Insulation Option	Uninsulated
Operating Temperature Range	649 °C[1200 °F]
Operation/Application	
Compatible With Wire Base Material	Nickel
Industry Standards	
Government Qualified Terminal	No
Packaging Features	
Packaging Quantity	500

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Colder Process Consolities	Not applicable for colder process capability

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent to these limits as defined in the Annexes of Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits

1-321897-5

Closed Ring Tongue Terminal, 22 – 16 AWG, #8 / M5 Stud Size, 5.2 mm [.205 in] Stud Diameter, Closed Barrel, Straight, STRATO-THERM DIAMOND GRIP




as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach


Compatible Parts



Also in the Series | STRATO-THERM DIAMOND GRIP



Customers Also Bought



1-321897-5

Closed Ring Tongue Terminal, 22 – 16 AWG, #8 / M5 Stud Size, 5.2 mm [.205 in] Stud Diameter, Closed Barrel, Straight, STRATO-THERM DIAMOND GRIP





Documents

Product Drawings DG 22-16 HT ALUMEL R M5

English

CAD Files

Customer View Model ENG_CVM_CVM_1-321897-5_U.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-321897-5_U.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-321897-5_U.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages RADIATION_RESISTANT_PRE-INSULATED_TERMINALS_SPLICES

English

Product Environmental Compliance

Product Compliance

English

Product Compliance

English