
1-382811-6 - ACTIVE

AMPMODU

TE Internal #: 1-382811-6 Board-to-Board Jumpers & Shunts, Economy, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -85 – 221 °F [-65 – 105 ° C]

View on TE.com >

Connectors > PCB Connectors > Board-to-Board Connectors > Board-to-Board Jumpers & Shunts



Shunt Type: Economy Shunt Style: Open Top Connector System: Board-to-Board Number of Positions: 2

Centerline (Pitch): 2.54 mm [.1 in]

Features



Product Type Features

Connector System	Board-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	2
Electrical Characteristics	
Insulation Resistance	1000 MΩ
Body Features	
Handle	Without
Primary Product Color	Black
Contact Features	
Contact Mating Area Plating Material Thickness	.381 μm[15 μin]
Contact Mating Area Plating Material	Gold
Contact Base Material	Phosphor Bronze

C For support call+1 800 522 6752

Board-to-Board Jumpers & Shunts, Economy, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -85 – 221 °F [-65 – 105 °C]



Shunt Type	Economy
Shunt Style	Open Top
Contact Current Rating (Max)	3 A
Housing Features	
Housing Material	Polyester - GF
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Product Height	6.35 mm[.25 in]
Usage Conditions	
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]
Operation/Application	
Circuit Application	Signal
Industry Standards	
Approved Standards	CSA Certified, UL Recognized
UL Flammability Rating	UL 94V-0
Packaging Features	
Jumper & Shunt Packaging	Loose Piece

1	\sim	0	

Packaging Quantity	1500
Packaging Method	Box

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Not applicable for solder process capability

Board-to-Board Jumpers & Shunts, Economy, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -85 – 221 °F [-65 – 105 °C]



Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



			€ =TE
TE Part #4-6609107-6 PS0S0SSXA=C1100	TE Part #1-745495-7 25 HDE MS RCPT,26-30,LEAD FREE	TE Part #5557572-3 MOD JK ASSY,6PORT,8POSN,SHLD	TE Part #3-1469373-7 ATCA GUIDE MODULE RA FEMALE
	ETE	Solution of the second	ETE
TE Part #6339488-1 VERTICAL BATTERY CONNECTOR ASSY	TE Part #2-111623-6 50, 2MM, POL,30 DP, LEAD FREE	TE Part #5390377-5 50 POS A/P PLUG 25 CL 30AU	TE Part #5749210-5 50 50SR CABLE RCPT ASSY

Board-to-Board Jumpers & Shunts, Economy, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -85 – 221 °F [-65 – 105 °C]





Documents

Product Drawings SHUNT, ECON, PHBR 15AU, BLACK L/P

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-382811-6_P.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-382811-6_P.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-382811-6_P.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages AMPMODU_INTERCONNECTION_SYSTEM_SECTION_6_7AND8

English

Product Specifications

Product Specification

English

Product Environmental Compliance MD_1-382811-6_11192018826_dmtec English MD_1-382811-6_11192018826_dmtec English Instruction Sheets Instruction Sheets Instruction Sheet (U.S.) English Low Profile, Economy, and Dual Beam Shunt Connectors 382811, 390088, and 382823

& For support call+1 800 522 6752

Board-to-Board Jumpers & Shunts, Economy, Open Top, 2 Position, .1 in [2.54 mm] Centerline, Signal, -85 – 221 °F [-65 – 105 °C]



English