1-794615-0 - ACTIVE

MATE-N-LOK | Micro MATE-N-LOK

TE Internal #: 1-794615-0 Rectangular Power Connectors, Housing, Plug, Wire-to-Wire / Wireto-Panel, 10 Position, 3 mm [.118 in] Centerline, Wire & Cable, Micro MATE-N-LOK

View on TE.com >

Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: Housing Connector & Housing Type: Plug Connector System: Wire-to-Panel, Wire-to-Wire Number of Positions: 10

Centerline (Pitch): 3 mm [.118 in]

Features



Product Type Features

Rectangular Power Connector Type	Housing				
Connector & Housing Type	Plug				
Connector System	Wire-to-Panel, Wire-to-Wire				
Sealable	No				
Connector & Contact Terminates To	Wire & Cable				
Configuration Features					
Number of Positions	10				
Number of Rows	2				
Electrical Characteristics					
Operating Voltage	250 VDC				
Contact Features					
Contact Retention Within Housing	Without				
Contact Type	Pin				

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire / Wire-to-Panel, 10 Position, 3 mm [.118 in] Centerline, Wire & Cable, Micro MATE-N-LOK



Termination Features

Termination Method to Wire & Cable	Crimp						
Mechanical Attachment							
Strain Relief	Without						
Mating Alignment Type	Polarization						
Mating Retention	With						
Mating Alignment	With						
Panel Mount Feature	With						
Panel Mount Feature Type	Locking Latch						
Mating Retention Type	Locking Tab						
Connector Mounting Type	Panel Mount						
Housing Features							
Centerline (Pitch)	3 mm[.118 in]						
Housing Color	Black						
Housing Material	Nylon						
Dimensions							

Panel Thickness (Recommended)

1.57 – 2.3 mm[.062 – .091 in]

Compatible Insulation Diameter (Max)	1.52 mm[.06 in]
Connector Height	8.71 mm
Product Width	16.89 mm
Product Length	24.85 mm
Row-to-Row Spacing	3 mm[.118 in]
Usage Conditions	
Operating Temperature Range	-40 – 105 °C[-40 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
CSA Rating	Certified, LR 7189
UL Rating	Recognized
Agency/Standard	CNR, USR
Approved Standards	UL E28476, VDE 40005280
UL Flammability Rating	UL 94V-0

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire / Wire-to-Panel, 10 Position, 3 mm [.118 in] Centerline, Wire & Cable, Micro MATE-N-LOK



Glow Wire Rating	Standard Part - Not Glow Wire			
Packaging Features				
Packaging Quantity	500			
Packaging Method	Bag			
Product Compliance For compliance documentation, visit the product page on TE.com>				
EU RoHS Directive 2011/65/EU	Compliant			
EU ELV Directive 2000/53/EC	Compliant No Restricted Materials Above Threshold			
China RoHS 2 Directive MIIT Order No 32, 2016				
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC			
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free			
Solder Process Capability	Not applicable for solder process capability			

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Rectangular Power Connectors, Housing, Plug, Wire-to-Wire / Wire-to-Panel, 10 Position, 3 mm [.118 in] Centerline, Wire & Cable, Micro MATE-N-LOK



Also in the SeriesMicro MATE-N-LOKImage: Series Se

Customers Also Bought



TE Part #1-794609-1	TE Part #2-794615-4	TE Part #1-794615-6	TE Part #794615-2	
PIN CONT 26-30 15 GOLD STRIP	PANEL MT DBL ROW HSG 24 POS	PANEL MT DBL ROW HSG 16 POS	PANEL MT DBL ROW HSG 2 POS	



Documents

Product Drawings PANEL MT DBL ROW HSG 10 POS

English

CAD Files

3D PDF

3D

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire / Wire-to-Panel, 10 Position, 3 mm [.118 in] Centerline, Wire & Cable, Micro MATE-N-LOK



Customer View Model

ENG_CVM_CVM_1-794615-0_C1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-794615-0_C1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-794615-0_C1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English

MICRO MATE-N-LOK CONNECTOR SYSTEM

English

Product Specifications

Application Specification

English

Product Environmental Compliance MD_1-794615-0_02242017332_dmtec

English

MD_1-794615-0_02242017332_dmtec

English