1-794615-4 ACTIVE

MATE-N-LOK | Micro MATE-N-LOK

TE Internal #: 1-794615-4

Rectangular Power Connectors, Housing, Plug, Wire-to-Wire / Wire-

to-Panel, 14 Position, 3 mm [.118 in] Centerline, Wire & Cable,

Micro MATE-N-LOK

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors











Rectangular Power Connector Type: Housing

Connector & Housing Type: Plug

Connector System: Wire-to-Panel, Wire-to-Wire

Number of Positions: 14

Centerline (Pitch): 3 mm [.118 in]

Features

Product Type Features

Rectangular Power Connector Type Housing Connector & Housing Type Plug Connector System Wire-to-Panel, Wire-to-Wire Sealable No Connector & Contact Terminates To Wire & Cable Configuration Features Number of Positions 14 Number of Rows 2 Electrical Characteristics Operating Voltage 250 VDC Contact Features Contact Retention Within Housing Without		
Connector System Sealable No Connector & Contact Terminates To Wire & Cable Configuration Features Number of Positions Number of Rows 2 Electrical Characteristics Operating Voltage Contact Features Wire-to-Panel, Wire-to-Wire No 2 Electro-Panel, Wire-to-Panel, Wire-to-Panel, Wire-to-Wire No 2 Electro-Panel, Wire-to-Panel, Wire-to-Panel, Wire-to-Wire No 2 Electro-Panel, Wire-to-Panel, Wire-to-Panel, Wire-to-Wire No 2 Configuration Features	Rectangular Power Connector Type	Housing
Sealable No Connector & Contact Terminates To Wire & Cable Configuration Features Number of Positions 14 Number of Rows 2 Electrical Characteristics Operating Voltage 250 VDC Contact Features	Connector & Housing Type	Plug
Connector & Contact Terminates To Configuration Features Number of Positions Number of Rows 2 Electrical Characteristics Operating Voltage Contact Features Wire & Cable Wire & Cable	Connector System	Wire-to-Panel, Wire-to-Wire
Configuration Features Number of Positions 14 Number of Rows 2 Electrical Characteristics Operating Voltage 250 VDC Contact Features	Sealable	No
Number of Positions 14 Number of Rows 2 Electrical Characteristics Operating Voltage 250 VDC Contact Features	Connector & Contact Terminates To	Wire & Cable
Number of Rows 2 Electrical Characteristics Operating Voltage 250 VDC Contact Features	Configuration Features	
Electrical Characteristics Operating Voltage 250 VDC Contact Features	Number of Positions	14
Operating Voltage 250 VDC Contact Features	Number of Rows	2
Contact Features	Electrical Characteristics	
	Operating Voltage	250 VDC
Contact Retention Within Housing Without	Contact Features	
	Contact Retention Within Housing	Without

Pin

Contact Type



Termination Features

Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Strain Relief	Without
Mating Alignment Type	Polarization
Mating Retention	With
Mating Alignment	With
Panel Mount Feature	With
Panel Mount Feature Type	Locking Latch
Mating Retention Type	Locking Tab
Connector Mounting Type	Panel Mount
Housing Features	
Centerline (Pitch)	3 mm[.118 in]
Housing Color	Black
Housing Material	Nylon
Dimensions	
Panel Thickness (Recommended)	1.57 – 2.3 mm[.062 – .091 in]
Compatible Insulation Diameter (Max)	1.52 mm[.06 in]
Connector Height	8.71 mm
Product Width	16.89 mm
Product Length	18.85 mm
Row-to-Row Spacing	3 mm[.118 in]
Usage Conditions	
Operating Temperature Range	-40 - 105 °C[-40 - 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
CSA Rating	Certified, LR 7189
UL Rating	Recognized
Agency/Standard	CNR, USR
Approved Standards	UL E28476, VDE 40005280
UL Flammability Rating	UL 94V-0



Packaging Features

Packaging Quantity	500
Packaging Method	Bag

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





Also in the Series | Micro MATE-N-LOK







Power Contacts(27)



Rectangular Power Connectors(466)

Customers Also Bought



TE Part #66566-4 III+ PIN,24-20,30AU/FL,LP



TE Part #6609007-3 20EEJ1=F7892A S0



TE Part #2-794617-2 22POS,MICRO MNL,RCPT HSG





TE Part #2-794617-0 20POS,MICRO MNL,RCPT HSG



TE Part #794615-6 PANEL MT DBL ROW HSG 6 POS



TE Part #1-794615-8 PANEL MT DBL ROW HSG 18 POS





TE Part #6578596-3 31-019476-000D, CABLE ASSEMBLY

Documents

Product Drawings

PANEL MT DBL ROW HSG 14 POS

English

CAD Files

3D PDF

3D



Customer View Model

ENG_CVM_CVM_1-794615-4_C1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1-794615-4_C1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-794615-4_C1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

Datasheets & Catalog Pages

SOFT_SHELL_PIN_AND_SOCKET_CONNECTORS_CATALOG

English

MICRO MATE-N-LOK CONNECTOR SYSTEM

English

Product Specifications

Application Specification

English

Product Environmental Compliance

TE Material Declaration

English