## AMP | Junior Timer

TE Internal #: 1-827578-1

Housing for Male Terminals, Wire-to-Wire, 3 Position, .197 in [5 mm] Centerline, Black, Wire & Cable, Power, Cable Mount (Free-

Hanging), Junior Timer

View on TE.com >



Connectors > Automotive Connectors > Automotive Housings > Timer Connector Housing



Connector System: Wire-to-Wire

Number of Positions: 3

Connector & Housing Type: Housing for Male Terminals

Centerline (Pitch): 5 mm [.197 in]

Sealable: No

All Timer Connector Housing (585)

## **Features**

## **Product Type Features**

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Wire
Connector & Housing Type	Housing for Male Terminals
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	Integrated in Housing
Configuration Features	
Number of Positions	3
Number of Rows	1
Electrical Characteristics	
Nominal Voltage Architecture	12 V, 24 V
Body Features	
Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	Neutral



#### **Contact Features**

Contact Size	2.8mm
Contact Type	Tab
Contact Current Rating (Max)	30 A

### Mechanical Attachment

Terminal Position Assurance	No
Strain Relief	Without
Mating Alignment Type	Polarization Slot
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

## **Housing Features**

Housing Material	PA GF
Centerline (Pitch)	5 mm[.197 in]

#### **Dimensions**

Connector Height	24.5 mm[.964 in]
Product Width	27.7 mm[1.09 in]
Product Length	30.5 mm[1.2 in]

## **Usage Conditions**

Operating Temperature (Max)	130 °C[266 °F]
Operating Temperature Range	-40 – 130 °C[-40 – 266 °F]

## Operation/Application

Circuit Application	Power	
Circuit / ipplication	1 OVVC1	

## Packaging Features

Packaging Quantity	500	
Packaging Method	Bag	

### Other

Serviceable	No	
Connector Position Assurance Capable	No	

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
------------------------------	-----------



EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	BFR/CFR/PVC Free, but Br/Cl >900 ppm in other sources.
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach


## Compatible Parts





## Also in the Series | Junior Timer







# Customers Also Bought

Housing for Male Terminals, Wire-to-Wire, 3 Position, .197 in [5 mm] Centerline, Black, Wire & Cable, Power, Cable Mount (Free-Hanging), Junior Timer



















TE Part #GV-16
GASKETS FOR SIZE 16 AS
CONNECTOR

### **Documents**

**Product Drawings** 

3P JUNIOR-TIMER GH

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-827578-1\_K.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-827578-1\_K.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-827578-1\_K.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

Housing for Male Terminals, Wire-to-Wire, 3 Position, .197 in [5 mm] Centerline, Black, Wire & Cable, Power, Cable Mount (Free-Hanging), Junior Timer



Timer Interconnection System

English