# 1-928776-4 ACTIVE

### AMPMODU | AMPMODU Headers

TE Internal #: 1-928776-4

Connector Contact, Pin, Wire-to-Board, Gold, Strip, Printed Circuit

Board, 5 A, Signal, Board Mount, -85 – 257 °F [-65 – 125 °C],

AMPMODU Headers

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Contacts



Contact Type: Pin

Connector System: Wire-to-Board

Contact Mating Area Plating Material: Gold

Packaging Method: Strip

Connector & Contact Terminates To: Printed Circuit Board

Rectangular Termination Post & Tail Thickness

### **Features**

### **Product Type Features**

Applied Pressure	Standard
Connector System	Wire-to-Board
Connector & Contact Terminates To	Printed Circuit Board
Contact Features	
Contact Mating Area Length	10 mm[.394 in]
Mating Square Post Dimension	.64 mm[.025 in]
PCB Contact Termination Area Plating Material Thickness	5 μm
Contact Mating Area Plating Material Thickness	.8 μm
Contact Shape & Form	Square
Contact Orientation	Straight
Contact Underplating Material	Nickel
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Phosphor Bronze
Contact Type	Pin
Contact Mating Area Plating Material	Gold
Contact Current Rating (Max)	5 A
Termination Features	

.64 mm[.025 in]



Rectangular Termination Post & Tail Width	.71 mm[.027 in]
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
Wire Insulation Support	Without
Connector Mounting Type	Board Mount
Usage Conditions	
Operating Temperature Range	-65 – 125 °C[-85 – 257 °F]
Operation/Application	
Circuit Application	Signal
Packaging Features	
Packaging Quantity	50000
Packaging Method	Strip

### **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2023 (233) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach



# **Compatible Parts**



TE Part # CAT-P100
Pin Insertion Machine P100









## Also in the Series | AMPMODU Headers




PCB Connector Mounting(1)




PCB Connector Shrouds(1)




PCB Headers & Receptacles(5010)



PCB Latches, Locks & Retainers(2)



Wire-to-Board Connector Assemblies & Housings(5)



Customers Also Bought




















TE Part #3-508368-7 ZYL.STIFT M3+8

TE Part #5-539949-3 LAGERBOCK BEARING H

### **Documents**

#### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-928776-4\_Y.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-928776-4\_Y.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-928776-4\_Y.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### **Product Environmental Compliance**

**Product Compliance Document** 

English

**Product Compliance Document** 

English

Connector Contact, Pin, Wire-to-Board, Gold, Strip, Printed Circuit Board, 5 A, Signal, Board Mount, -85 – 257 °F [-65 – 125 °C], AMPMODU Headers

