
1-969508-2 - ACTIVE

MQS

TE Internal #: 1-969508-2 Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 6 Position, .1 in [2.54 mm] Centerline, Black, Wire & Cable, Signal, MQS

View on TE.com >

Connectors > Automotive Connectors > Automotive Housings > MQS, CONNECTOR HOUSING



Connector System: Wire-to-Board, Wire-to-Wire

Number of Positions: 6

Connector & Housing Type: Housing for Female Terminals

Centerline (Pitch): 2.54 mm [.1 in]

Sealable: No

All MQS, CONNECTOR HOUSING (573)

E

Features

Prod	luct ⁻	Features	5
			-

Mixed & Hybrid Connector	No
Connector Shape	Rectangular
Connector System	Wire-to-Board, Wire-to-Wire
Connector & Housing Type	Housing for Female Terminals
Sealable	No
Connector & Contact Terminates To	Wire & Cable
Primary Locking Feature	On the Terminal
Configuration Features	
Number of Positions	6
Number of Rows	1
Electrical Characteristics	
Operating Voltage	24 VDC

Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 6 Position, .1 in [2.54 mm] Centerline, Black, Wire & Cable, Signal, MQS



Nominal Voltage Architecture	12 V, 24 V
Body Features	
Cable Exit Angle	180°
Primary Product Color	Black
Connector & Keying Code	A
Contact Features	
Contact Size	.63mm
Contact Type	Socket
Mating Tab Width	.63 mm[.025 in]
Contact Current Rating (Max)	7.5 A
Mechanical Attachment	
Terminal Position Assurance	Yes
Strain Relief	Without
Mating Alignment Type	Keyed
Mating Alignment	With
Connector Mounting Type	Cable Mount (Free-Hanging)

Housing Features

Housing Material	PBT GF10
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Connector Height	10.6 mm[.417 in]
Product Width	16 mm[.63 in]
Product Length	17.7 mm[.697 in]
Usage Conditions	
Operating Temperature (Max)	120 °C[248 °F]
Operating Temperature Range	-40 - 120 °C[-40 - 248 °F]
Operation/Application	
Circuit Application	Signal
Other	
Serviceable	Yes
Connector Position Assurance Capable	No

Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 6 Position, .1 in [2.54 mm] Centerline, Black, Wire & Cable, Signal, MQS



Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-onreach


Compatible Parts



Also in the Series MQS

Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 6 Position, .1 in [2.54 mm] Centerline, Black, Wire & Cable, Signal, MQS







PCB Headers & Receptacles(213)

Customers Also Bought



Housing for Female Terminals, Wire-to-Wire / Wire-to-Board, 6 Position, .1 in [2.54 mm] Centerline, Black, Wire & Cable, Signal, MQS





Documents

Product Drawings 6POS MQS REC COD A

English

CAD Files

Customer View Model ENG_CVM_CVM_1-969508-2_C.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1-969508-2_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1-969508-2_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages Micro Quadlok Interconnection System (MQS)

English

Product Specifications Application Specification

English