
1123688-3 - ACTIVE

TE Internal #: 1123688-3 DC Jack Connectors, Board-to-Board, 6 Position, .098 in [2.5 mm] Centerline, Receptacle, 30 VDC, Vertical, Printed Circuit Board, Power & Signal

View on TE.com >

Connectors > PCB Connectors > Battery Connectors & Holders > DC Jack Connectors



Connector System: Board-to-Board Number of Positions: 6

Centerline (Pitch): 2.5 mm [.098 in]

Connector & Housing Type: Receptacle

Operating Voltage: 30 VDC

Features

Product Type Features



Connector System	Board-to-Board
Connector & Housing Type	Receptacle
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	6
PCB Mount Orientation	Vertical
Electrical Characteristics	
Operating Voltage	30 VDC
Contact Features	
Contact Current Rating (Max)	6 A
Mechanical Attachment	
PCB Mount Retention	With
PCB Mount Retention Type	Locating Post
Connector Mounting Type	Board Mount

C For support call+1 800 522 6752

1123688-3

DC Jack Connectors, Board-to-Board, 6 Position, .098 in [2.5 mm] Centerline, Receptacle, 30 VDC, Vertical, Printed Circuit Board, Power & Signal



Housing Features	
Centerline (Pitch)	2.5 mm[.098 in]
Usage Conditions	
Operating Temperature Range	-20 - 80 °C[-4 - 176 °F]
Operation/Application	
Circuit Application	Power & Signal
Packaging Features	
Packaging Quantity	70
Packaging Method	Tray
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2021

(211)

Does not contain REACH SVHC

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Solder Process Capability

Halogen Content

Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts


1123688-3

DC Jack Connectors, Board-to-Board, 6 Position, .098 in [2.5 mm] Centerline, Receptacle, 30 VDC, Vertical, Printed Circuit Board, Power & Signal





Customers Also Bought



Documents

Product Drawings

2.5 BATTERY REC ASSY 6P

English

CAD Files

Customer View Model ENG_CVM_CVM_1123688-3_P.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1123688-3_P.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1123688-3_P.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use

1123688-3

DC Jack Connectors, Board-to-Board, 6 Position, .098 in [2.5 mm] Centerline, Receptacle, 30 VDC, Vertical, Printed Circuit Board, Power & Signal



Datasheets & Catalog Pages

POWER_CONNECTORS_CATALOG_SEC09_LAPTOPS_PORTABLES

English

2_PIECE_POWER_CONNECTORS_qrg_4-1773458-1

English

Product Specifications

Product Specification

English

2.5mm Pitch Battery Pack Connector

English