1375820-3 ✓ ACTIVE

CST

TE Internal #: 1375820-3

Housing, Receptacle, Wire-to-Wire, 3 Position, .1 in [2.54 mm] Centerline, Crimp, 1 Row, Natural, Mating Retention, Wire & Cable,

Power & Signal

View on TE.com >



Connectors > PCB Connectors > Wire-to-Board Connectors > Wire-to-Board Connector Assemblies & Housings > Receptacle Housing: 2.54mm, 1 Row, CST-100 II











Connector Product Type: Housing

Connector & Housing Type: Receptacle

Connector System: Wire-to-Wire

Number of Positions: 3

Centerline (Pitch): 2.54 mm [.1 in]

All Receptacle Housing: 2.54mm, 1 Row, CST-100 II (25)

Features

Product Type Features

Connector & Housing Type Receptacle Wire to Wire	Connector Product Type	Housing
Connector System	Connector & Housing Type	Receptacle
Connector system	Connector System	Wire-to-Wire
Sealable	Sealable	No
Connector & Contact Terminates To Wire & Cable	Connector & Contact Terminates To	Wire & Cable

Configuration Features

Number of Positions	3
Number of Rows	1

Electrical Characteristics

Operating Voltage	250 VAC	

Body Features



Primary Product Color	Natural
Contact Features	
Contact Retention Within Housing	Without
Contact Layout	Inline
Contact Type	Socket
Contact Current Rating (Max)	7 A
Termination Features	
Termination Method to Wire & Cable	Crimp
Mechanical Attachment	
Strain Relief	Without
PCB Mount Alignment	Without
Panel Mount Feature	Without
PCB Mount Retention	Without
Mating Retention Type	Latch
Mating Retention	With
Connector Mounting Type	Cable Mount (Free-Hanging)
Housing Features	
Housing Material	Nylon - GF
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Connector Length	8.13 mm[.32 in]
Connector Height	6.6 mm[.26 in]
Wire Size	.13 – .33 mm²
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal
Industry Standards	
Glow Wire Rating	Standard Part - Not Glow Wire
Agency/Standard	CSA, UL
UL Flammability Rating	UL 94V-0



Packaging Quantity	1
Packaging Method	Package
Other	
Discrete Wire Connector Comment	Accepts Rec Contact p/n 1375819 & MTA-100 Keying Plug P/N 641994-1, Not interchangeable with CST-100 contacts and housings.

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts





TE Part # CAT-104MTA-PVUNH
PCB Header: Polyester, Vertical,
Unshrouded, No Mating Alignment



TE Part # CAT-104MTA-NYLCC Nylon PCB Connector Covers: 2.54 mm, MTA 100



TE Part # CAT-104MTA-PLSCC
Polyester PCB Connector Covers: 2.54
mm, MTA 100



TE Part # CAT-104MTA-PRUSH
PCB Header: Polyester, Right Angle,
Unshrouded



TE Part # CAT-104MTA-PVUMH
PCB Header: Polyester, Vertical, 2.54
mm



TE Part # CAT-104MTA-NVSMH Nylon Vertical PCB Header: 2.54mm, Surface Mount, MTA 100



TE Part # CAT-104MTA-PVBRH
Polyester Vertical PCB Header: 2.54
mm, Breakaway, MTA 100



TE Part # CAT-104MTA-PRUMH
PCB Header: Polyester, Right Angle,
2.54 mm



TE Part # CAT-104MTA-NRTHH
PCB Header: Nylon, Right Angle, 2.54
mm



TE Part # 3-644893-3 03P CST100 SHRD HDR ASSY LF



TE Part # 3-644894-3 03P CST100 SHRD HDR ASSY LF



TE Part # CAT-104MTA-NVTHH

Nylong Vertical PCB Header: 2.54mm,
Through Hole, MTA 100



TE Part # 3-644892-3 03P CST100 SHRD HDR ASSY LF



TE Part # 3-644898-3 03P CST100 SHRD HDR ASSY LF

Customers Also Bought



















Documents

Product Drawings

CST-100 II HOUSING 3 POS

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_1375820-3_A.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_1375820-3_A.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_1375820-3_A.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Product Environmental Compliance

Product Compliance Document

English

Product Compliance Document

English

Instruction Sheets

Instruction Sheet (U.S.)

English

Agency Approvals

CSA Certificate

English