1393303-9 - ACTIVE

Power Relay F TE Internal #: 1393303-9 Mini Relays, 24 VDC Coil Voltage, 30 – 50 A, 1 Form A (NO), Plug-In, 324 Ω Coil Resistance, Power Relay F

View on TE.com >



Relays, Contactors & Switches > Relays > Automotive Relays > Automotive Plug-In Relays > Mini Relays



Rated Coil Voltage: 24 VDC Mini Relay Contact Current Class: 30 – 50 A Mini Relay Contact Arrangement: 1 Form A (NO) Mini Relay Mounting Type: Plug-In Mini Relay Coil Resistance: 324 Ω

Features

Product Type Features

Relay Туре	Power Relay F4
Electrical Characteristics	
Current Rating (85°C)	20 A
Coil Power Rating Class	>1.5W W
Contact Limiting Short-Time Current	240 A
Insulation Initial Dielectric Between Contacts and Coil	500 Vrms
Insulation Initial Dielectric Between Coil/Contact Class	0 – 500 V
Insulation Initial Dielectric Between Open Contacts	500 Vrms
Coil Magnetic System	Monostable, DC
Contact Limiting Making Current	120 A
Coil Power Rating (DC)	1800 mW
Contact Limiting Continuous Current	60 A
Rated Voltage	24 VDC
Contact Limiting Breaking Current	20 A
Contact Switching Load (Min)	1000mA @ 5VDC
Rated Coil Voltage	24 VDC
Mini Relay Coil Resistance	324 Ω
Body Features	
Weight	35 g[1.2 oz]

1393303-9

Mini Relays, 24 VDC Coil Voltage, 30 – 50 A, 1 Form A (NO), Plug-In, 324 Ω Coil Resistance, Power Relay F



Contact Features

Terminal Type	Plug-In, Quick Connect
Contact Base Material	Silver Alloy
Mini Relay Contact Current Class	30 – 50 A
Mini Relay Contact Arrangement	1 Form A (NO)
Mechanical Attachment	
Mini Relay Mounting Type	Plug-In
Dimensions	
Width Class (Mechanical)	25 – 30 mm
Height	24.9 mm[.98 in]
Length	25.9 mm[1.02 in]
Length Class (Mechanical)	25 – 30 mm
Width	25.9 mm[1.02 in]
Height Class (Mechanical)	20 – 25 mm
Usage Conditions	
Environmental Ambient Temperature Class	105 – 125°C
Environmental Ambient Temperature (Max)	125 °C[257 °F]

Other

Mounting Br	rackets
-------------	---------

Without

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Not Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) SVHC > Threshold: Pb (2.6% in Component Part) Aticle Safe Usage Statements! Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC

1393303-9

Mini Relays, 24 VDC Coil Voltage, 30 – 50 A, 1 Form A (NO), Plug-In, 324 Ω Coil Resistance, Power Relay F



Free

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



TE Part # 1-1904045-1 V23333Z0001A007-EV-100

Also in the Series | Power Relay F



Customers Also Bought



1393303-9

Mini Relays, 24 VDC Coil Voltage, 30 – 50 A, 1 Form A (NO), Plug-In, 324 Ω Coil Resistance, Power Relay F





Documents

Product Drawings

CAD Files Customer View Model ENG_CVM_1393303-9_S00F.2d_dxf.zip English Customer View Model ENG_CVM_1393303-9_S00F.3d_igs.zip English Customer View Model ENG_CVM_1393303-9_S00F.3d_stp.zip English

3D PDF

English

Datasheets & Catalog Pages

Automotive Relay Application Notes

English

Product Specifications Definitions General Purpose Relays

English